

EF 400mm f/4 DO IS II USM

Small in size, big on performance.

A high-performance super-telephoto lens that makes use of Diffractive Optics technology for a more compact, lightweight design.



- A lightweight, portable super telephoto lens that's ideal for photographers on the move
- Third generation Diffractive Optics (DO) deliver superb image quality, with improved resistance to flare and coloured fringing
- Shoot with shutter speeds up to 4 stops slower than normal, with a three-mode Image Stabilizer
- Keep fast-moving subjects pin sharp when shooting still photos. Power Focus technology allows pull-focus effects when shooting video
- Work instinctively for maximum creativity. Intuitive Focus Preset and Focus Stop buttons are right where you need them, and full-time manual focus override provides precise adjustment

Product Range



EF 400mm f/2.8L IS II USM



EF 400mm f/4 DO IS II USM



EF 400mm f/5.6L USM

EF 400mm f/2.8L IS II USM
EF 400mm f/4 DO IS II USM
EF 400mm f/5.6L USM

EF 400mm f/4 DO IS II USM

Small in size, big on performance.

A high-performance super-telephoto lens that makes use of Diffractive Optics technology for a more compact, lightweight design.

Sales Start Date: November 2014

Technical Specifications

OPTICAL FEATURES/SPECIFICATIONS

Angle of view (horzntl, vertl, diagnl)	5°10', 3°30', 6°10'
Lens construction (elements/groups)	18/12
No. of diaphragm blades	9
Minimum aperture	32
Closest focusing distance (m)	3.3
Maximum magnification (x)	0.13
Distance Information	Yes
Image stabilizer ¹⁵	4 stops
AF actuator	Ring USM ³

PHYSICAL SPECIFICATIONS

Dust/moisture resistance ⁴	Yes
Filter diameter (mm)	52 Drop in
Max. diameter x length (mm)	128 x 232.7
Weight (g)	2100

ACCESSORIES

Lens cap	E-145C
Lens hood	ET-120 (WII)
Lens case/pouch	Lens Case 400D
Rear cap	Lens Dust Cap E
Magnification with Extension Tube EF12 II	0.17-0.03
Magnification with Extension Tube EF25 II	0.22-0.07

Extender Compatibility	Compatible
Other Accessories	Canon drop-in 52mm filters

SPECIFICATIONS WITH EF 1.4X II

Focal Length	560
Maximum Aperture	5.6-45
Maximum Magnification	0.18
AF Possible	Yes
IS	Yes

SPECIFICATIONS WITH EF 2X II

Focal Length	800
Maximum Aperture	8-64
Maximum Magnification	0.26
AF Possible	Yes ¹¹
IS	Yes ¹²

Footnotes

^[4] Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

^[3] AF Full Time Manual Focus

^[11] AF possible with EOS-1 series only and 5D Mark III with firmware 1.2.1

^[12] IS will not work with the following cameras EOS-1, EOS 5, EOS 100, EF-M, EOS 1000/F/n/Fn, EOS 700, EOS 10, EOS RT, EOS 600/630, EOS 850, EOS 750, EOS 620, EOS 650

^[15] Tested under CIPA standards

Product Details:

Product name	Mercury Code	EAN Code
EF 400mm f/4 DO IS II USM	8404B005AA	4960999977270

Optional Accessories:

Product name	Mercury Code	EAN Code
LENS CASE 400D	8405B001AA	4960999977294

Measurement / Logistic Information:

Product name	Mercury Code	Pack type	Pack Description	Quantity	Length (mm)	Width (mm)	Height (mm)	Net Weight (kg)	Gross Weight (kg)
EF 400mm f/4 DO IS II USM	8404B005AA	EA	Each	1	488	367	400	5.033	6.408
		CT	Carton	N/A	N/A	N/A	N/A	N/A	N/A
		EP	Euro pallet	8	120	80	95		61.3
			Layers per pallet	2					
			Cartons per layer	4					
LENS CASE 400D	8405B001AA	EA	Each	1	488	367	400	2.530	3.7783
		CT	Carton	N/A	N/A	N/A	N/A	N/A	N/A
		EP	Euro pallet	8	120	80	95		40.2
			Layers per pallet	2					
			Cartons per layer	4					

What's in the box?

- EF 400mm f/4 DO IS II USM
- LENS HOOD ET-120 (WII)
- LENS CASE 400D
- LENS CAP E-145C
- LENS DUST CAP E
- LENS WIDE STRAP B
- DROP-IN GELATIN FILTER HOLDER 52 (WII)
- STRAP FOR HARD CASE
- Instruction Manuals (Booklet)
- Warranty card (EUR)

Canon Inc.
 canon.com
 Canon Europe
 canon-europe.com
 English edition
 Canon Europa NV 2014