

| EF-M 11-22mm f/4-5.6 IS STM | | |
|--|--|--|
| Optical Features/Specifications | | |
| | Image size | APS-C |
| | 35mm film equivalent focal length (mm) | 18-35 |
| | Angle of view (horzntl, vertl, diagnol) | 91°50'–54°30', 68°55'–37°50', 102°10'–63°30' |
| | Lens construction (elements/groups) | 12/9 |
| | No. of diaphragm blades | 7 |
| | Minimum aperture | 22 - 32 ² |
| | Closest focussing distance (m) | 0.15 |
| | Maximum magnification (x) | 0.30 (at 22mm) |
| | Distance Information | Provided |
| | Image stabilizer | 3-stops |
| | AF actuator | STM |
| Physical Specifications | | |
| | Dust/moisture resistance ⁴ | - |
| | Filter diameter (mm) | 55 |
| | Max. diameter x length (mm) | 60.9 x 58.2 ¹³ |
| | Weight (g) | 220 |
| Accessories | | |
| | Lens Cap | E-55 |
| | Lens hood | EW-60E |
| | Lens case/pouch | LP814 |
| | Maximum number of Hood III compatible with Gelatin Filter Holder III | - |
| | Maximum number of Hood IV compatible with Gelatin Filter Holder IV | - |
| | Magnification with Extension Tube EF12 II | - |
| | Magnification with Extension Tube EF25 II | - |
| | Extender Compatibility | NC |
| | Other Accessories | - |

² Minimum aperture if using 1/3stop increments

⁴ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

¹³ Lens dimensions when in retracted state