

PowerShot SX420 IS

Tiny connected bridge camera that's simple, fun and creative

Effortlessly capture the detail of every special moment in stunning photos and HD movies with this family-friendly mini bridge camera, which packs a big 42x zoom, Smart Auto, Wi-Fi and fun creative modes into a tiny body.



- A tiny, bridge-style camera with ergonomic grip that's easy to carry and gets you 42x closer to distant detail
- Effortlessly record superb HD movies (720p) with one touch of a button, while a Dynamic Image Stabilizer keeps your footage steady
- With Wi-Fi*, NFC and Wi-Fi Button it's simple to connect to your smart device, shoot remotely and share or back up your creations
- Enjoy exceptional, detailed images thanks to 20.0 Megapixels, DIGIC 4+ and an Intelligent Image Stabilizer
- Just point, shoot and get fantastic results thanks to Smart Auto with Auto Button and fun Creative Filters

* Wi-Fi connectivity and features vary by model and region

Product Range



PowerShot SX60 HS



PowerShot SX540 HS



PowerShot SX420 IS

PowerShot SX60 HS
PowerShot SX540 HS
PowerShot SX420 IS

Technical Specifications

IMAGE SENSOR

Type	1/2.3 type CCD
Effective Pixels	Approx. 20.0 M ⁽¹⁴⁾
Total Pixels	Approx. 20.5 M
Colour Filter Type	Primary Colour

IMAGE PROCESSOR

Type	DIGIC 4+ with iSAPS technology
------	--------------------------------

LENS

Focal Length	4.3 – 180.6 mm (35 mm equivalent: 24 – 1008 mm)
Zoom	Optical 42x ZoomPlus 84x Digital approx. 4x (with Digital Tele-Converter approx. 1.6x or 2.0x ⁽¹⁾) Combined approx. 164x

Maximum f/number Construction

f/3.5 - f/6.6
12 elements in 11 groups (3 UD lenses, 2 double-sided aspherical lenses, 1 single-sided aspherical lens)

Image Stabilisation

Yes (lens shift-type), approx. 2.5-stop ⁽¹³⁾. Intelligent IS plus Enhanced Dynamic IS

FOCUSING

Type	TTL
AF System/ Points	AiAF (Face Detection / 9-point), 1-point AF (fixed to centre)
AF Modes	Single, Continuous, Servo AF/AE ⁽⁶⁾ , Tracking AF
AF Point Selection	Size (Normal, Small)
AF Assist Beam	Yes
Closest Focusing Distance	0 cm (W) from front of lens in Macro

EXPOSURE CONTROL

Metering modes	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (Centre)
Exposure Compensation	+/- 2 EV in 1/3 stop increments. Enhanced i-Contrast for automatic dynamic range correction
ISO sensitivity	AUTO, 100, 200, 400, 800, 1600

SHUTTER

Speed	1 – 1/4000 sec. (factory default) 15 – 1/4000 s (total range – varies by shooting mode)
-------	--

WHITE BALANCE

Type	TTL
Settings	Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom

COLOUR MATRIX

Type	sRGB
------	------

LCD MONITOR

Monitor	7.5 cm (3.0") TFT, approx. 230,000 dots
Coverage	Approx. 100%
Brightness	Adjustable to one of five levels. Quick-bright LCD

FLASH

Modes	Auto, Manual Flash On / Off, Slow Synchro
Slow Sync Speed	Yes. Fastest speed 1/2000 s.
Red-Eye Reduction	Yes
Flash Exposure Compensation	Face Detection FE, Smart Flash Exposure
Flash Exposure Lock	Yes
Built-in Flash Range	50 cm – 5.0 m (W) / 1.4 m – 2.7 m (T)
External Flash	Canon High Power Flash HF-DC2

SHOOTING

Modes	Smart Auto (32 scenes detected), Program AE, Live View Control, Portrait, Face Self-Timer, Low Light (5.0MP), Fish-eye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect, Fireworks, Long Shutter
Modes in Movie	Smart Auto (21 scenes detected), Program AE, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Fireworks

Photo Effects

My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)

Drive modes

Single, Continuous, Self-Timer

Continuous Shooting

Approx. 0.5 shots/sec
Low Light Mode (5.0 MP): Approx. 2.2 shots/s (all speeds are until memory card becomes full) ⁽³⁾ ⁽⁴⁾

RECORDING PIXELS / COMPRESSION

Image Size

4:3 - (L) 5152 x 3864, (M) 2560 x 1920, (M1) 3648 x 2736, (M2) 2048 x 1536, (S) 640 x 480
16:9 - (L) 5152 x 2896, (M1) 3648 x 2048, (M2) 1920 x 1080, (S) 640 x 360
3:2 - (L) 5152 x 3432, (M1) 3648 x 2432, (M2) 2048 x 1368, (S) 640 x 424
1:1 - (L) 3856 x 3856, (M1) 2736 x 2736, (M2) 1536 x 1536, (S) 480 x 480

Compression

Superfine, Fine

Movies

(HD) 1280 x 720, 25 fps, (L) 640 x 480, 29.97 fps

Miniature Effect (HD) 5 fps, 2.5 fps, 1.25 fps

Miniature Effect (L) 6 fps, 3 fps, 1.5 fps

(Full HD & HD) Up to 4 GB or 29 min 59 sec ⁽⁷⁾

(L) Up to 4 GB or 1 hour ⁽⁴⁾

FILE TYPES

Still Image Type

JPEG compression (Exif 2.3 (Exif Print) compliant) / Design rule for Camera File system, Digital Print Order Format (DPOF) Version 1.1 compliant

Movies

MP4 (Video: MPEG4-AVC / H.264, Audio: MPEG4 AAC-LC (monaural))

DIRECT PRINT

Canon Printers

Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge

PictBridge

Yes (via USB or Wireless LAN)

OTHER FEATURES

GPS

GPS via mobile (via Canon Camera Connect app with compatible smart devices)

Red-Eye Correction

Yes, during shooting and playback

Intelligent Orientation Sensor

Yes, with Auto Rotate

Histogram

Yes, during playback

Playback zoom

Approx. 2x – 10x

Self Timer

Approx. 2, 10 s or Custom

Menu Languages

English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese, Hebrew

INTERFACE

Computer

Hi-Speed USB composite connector (Mini-B compatible)

Other

A/V output, composite connector (PAL/NTSC)

Computer / Other

Wi-Fi (IEEE802.11b/g/n), (2.4 GHz only), with Dynamic NFC support ⁽¹¹⁾

MEMORY CARD

Type

SD, SDHC, SDXC

SUPPORTED OPERATING SYSTEM

PC & Macintosh

Windows 10 / 8.1 / 8 / 7 SP1 ⁽¹⁶⁾

Mac OS X 10.9 / 10.10 / 10.11

For Wi-Fi connection to a PC:

Windows 10 / 8.1 / 8 / 7 SP1

Mac OS X 10.9 / 10.10

For Image Transfer Utility:

Windows 10 / 8.1 / 8 / 7 SP1

Mac OS X 10.9 / 10.10 / 10.11

CameraWindow DC

Map Utility

Image Transfer Utility

Other

Camera Connect app available on iOS and Android devices

Technical Specifications

POWER SOURCE

Batteries

Rechargeable Li-ion Battery NB-11LH
(battery and charger supplied)

Battery life

Approx. 195 shots
Eco mode approx. 260 shots
Approx. 300 min playback

ACCESSORIES

Cases / Straps

Soft Case DCC-950
PowerShot Accessory Organizer

Flash

Canon High Power Flash HF-DC2

Power Supply & Battery

Battery Charger CB-2LFE

Chargers

Rechargeable Li-ion Battery NB-11LH

Other

Canon AV cable AVC-DC400

Interface Cable IFC-400PCU

PHYSICAL SPECIFICATIONS

Operating Environment

0 – 40 °C, 10 – 90 % humidity

Dimensions (W x H x D)

104.4 x 69.1 x 85.1 mm

Weight

Approx. 325 g (including battery and memory card)

⁽¹⁾ Depending on the image size selected.

⁽³⁾ Under conditions where the flash does not fire.

⁽⁴⁾ Depending on memory card speed / capacity / compression setting.

⁽⁶⁾ Some settings limit availability.

⁽⁷⁾ The following Speed Class memory cards are required for maximum record time:
(HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above.
(iFrame) 1280 x 720 Speed Class 6

⁽¹¹⁾ Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region. For more information visit www.canon-europe.com/wirelesscompacts

⁽¹³⁾ Values at maximum optical focal length. Cameras whose focal length exceeds 350 mm (35 mm equivalent) are measured at 350 mm.

⁽¹⁴⁾ Image processing may cause a decrease in the number of pixels.

⁽¹⁸⁾ Software applications compatible with Windows 10 in Windows 10 Desktop Mode only.

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.

Subject to change without notice.

PowerShot SX420 IS

Tiny connected bridge camera that's simple, fun and creative

Effortlessly capture the detail of every special moment in stunning photos and HD movies with this family-friendly mini bridge camera, which packs a big 42x zoom, Smart Auto, Wi-Fi and fun creative modes into a tiny body.

Sales Start Date: mid-February 2016



Product Details:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PowerShot SX420 IS black	1068C002	4549292056488	CHF 259.00
PowerShot SX420 IS red	1069C002	4549292056556	CHF 259.00

Optional Accessories:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Power Supply			
Battery Pack NB-11LH	9391B001	4549292004472	CHF 68.00
Battery Charger CB-2LFE	8420B001	496099977324	CHF 88.00
Cables			
Interface Cable IFC-400PCU	9370A001	4960999209906	CHF 38.00
AV Cable AVC-DC400	2563B001	4960999570754	CHF 28.00
Flash			
High Power Flash HF-DC2	5189B001	4960999782232	CHF 158.00
Cases			
Soft case DCC-950	0037X615	8714574592121	CHF 38.00
Accessory Organizer	0036X433	8714574583167	CHF 28.00

Measurement / Logistic Information:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)
Digital Camera PowerShot SX420 IS BK EU23	1068C002AA	EA	Each	1	144	159	108	0.698
Digital Camera PowerShot SX420 IS RE EU23	1069C002AA	CT	Carton	10	551	313	200	7.68
		EP	Euro Pallet	200	1200	800	1150	164
			Layers per pallet	5				
			Cartons per layer	4				
			Products per layer	40				

What's in the box?

- Digital Camera PowerShot SX420 IS
- Wrist Strap WS-DC12
- Battery Pack NB-11LH
- Battery Charger CB-2LFE
- AC Cable
- Lens Cap
- User Manual Kit

The Canon logo is displayed in its signature red font.