

# EOS M50

## DO YOUR STORIES JUSTICE

A sleek design classic, this mirrorless camera will inspire you to make memorable stories you'll be proud to share thanks to technologies like 4k movies, a DSLR sized sensor and effortless connectivity.



- Modern, hassle free shooting for superb results
- Compact, sleek and intuitive shooting experience
- Clever connectivity and control with Wi-Fi\* & Bluetooth\*\*
- Inspiring technologies for stories you'll be proud of
- Creative freedom to capture every story

**24.1** MEGA  
PIXELS  
CMOS



**Dual Pixel AF**  
CMOS

**10**  
Frames  
Per Sec



**OLED EVF**  
2,360k dots

### PRODUCT RANGE



EOS M6



EOS M50



EOS M100

EOS M5  
EOS M6  
**EOS M50**  
EOS M100

\*Wi-Fi: Not all functions or devices are supported; see full specifications for details.

\*\*Equipped with Bluetooth® low energy technology. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Canon Inc. is under license. Other trademarks and trade names are those of their respective owners. Initial pairing with compatible device required.

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS M50

## IMAGE SENSOR

Type	22.3 x 14.9mm CMOS
Effective Pixels	Approx. 24.1 megapixels
Total Pixels	Approx 25.8 megapixels
Aspect Ratio	3:2
Low-Pass Filter	Built-in/Fixed
Sensor Cleaning	EOS integrated cleaning system
Colour Filter Type	Primary Colour

## IMAGE PROCESSOR

Type	DIGIC 8
------	---------

## LENS

Lens Mount	EF-M (EF and EF-S lenses compatible via Mount adapter EF-EOS M)
Focal Length	Equivalent to 1.6x the focal length of the lens
Image Stabilisation	Optical Image Stabilizer on compatible lens

Movie: In-camera Digital IS available. Further stabilisation enhancements from lenses compatible with Dynamic IS

## FOCUSING

Type	Dual Pixel CMOS AF System. Phase detection pixels built onto imaging sensor <sup>[20]</sup>
	Contrast detection method is used during 4K Movie Servo AF
AF System/ Points	Maximum 143/99 points depending on lens.  Max 25 frames in Zone AF <sup>[15]</sup>

## AF working range

AF Modes	EV -2 - 18 (at 23 °C, ISO 100, with EF-M 22mm f/2 STM) One-Shot AF and Servo AF
AF Point Selection	Face + Tracking: Face and subject tracking via automatic recognition/ manual selection via touchscreen. Automatic selection over AF points when no face recognised within frame.

Eye AF available in One Shot AF

Smooth Zone AF: Manual zone selection, plus automatic selection over AF points within selected zone

1-point AF: Manual selection via touchscreen/ buttons

## Selected AF point display

AF Lock	Indicated on LCD monitor/ EVF Locked when shutter button is pressed half way or customisable AE Lock Button
---------	--

## AF Assist Beam

Manual Focus	via LED assist beam
--------------	---------------------

With EF & EF-S lenses - Select via AF/MF switch on lens

With EF-M lenses - Select via dedicated MF Button/ other customisable buttons (toggle AF/MF).  
  
MF Peaking available  
AF+MF available (Manual focus adjustment after One-Shot AF)  
Magnify image available during MF (5x or 10x)

## EXPOSURE CONTROL

Metering modes	Real-time metering from the image sensor (1) Evaluative metering (384 zones) (2) Partial metering at center (approx. 6.4% of Live View Screen) (3) Center weighted average metering (4) Spot metering (approx. 2.8% of Live View Screen)
----------------	--

## Metering Range

Center weighted only in Movie recording  
Still image: EV 0 - 20 (at 23 °C, ISO 100)  
Movie: EV 0 - 20 (at 23 °C, ISO 100)

## AE Lock

Auto: In One-shot AF mode with evaluative metering exposure is locked when focus is achieved.  
Manual: By AE Lock Button in creative zone modes.  
+/-3 EV in 1/3 stop increments  
3 shots, +/- 2 EV, 1/3-stop increments (can be used together with Exposure Compensation)  
ISO AUTO (100 - 6400), 100 - 25600 in 1/3 stop increments. ISO can be expanded to 51200

## Exposure Compensation

### AEB

## ISO Sensitivity (8)

4K Movie: ISO AUTO (100 - 6400), 100 - 6400 in 1/3-stop increments. Full HD and HD Movie: ISO AUTO (100 - 12800), ISO 100 - 12800 in 1/3-stop increments. ISO can be expanded to 25600

## SHUTTER

Type	Electronically controlled focal-plane shutter
Speed	30 - 1/4000 sec (1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)

## WHITE BALANCE

Type	Auto white balance with the imaging sensor
Settings	Auto (Ambience Priority), Auto (White Priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature (100 Kelvin increments)

White balance compensation:  
1. Blue/Amber +/-9 levels  
2. Magenta/ Green +/-9 levels

Yes, 1 setting can be registered

## Custom White Balance

## VIEWFINDER

Type	0.39-type OLED Electronic Viewfinder Approx. 2,360,000 dots
------	--

## Coverage (Vertical/Horizontal)

Eyepoint	Approx 100%
----------	-------------

## Dioptr Correction

Yes

## Viewfinder Information

Customisable and toggle via INFO. Button  
(1) Liveview image with exposure info  
(2) Liveview image with basic info  
(3) Liveview image with full info

Customisable settings:  
Grid overlay (x3 formats), Histogram (Brightness/ RGB), Electronic Level, Multi aspect ratios  
Yes

## Depth of field preview

## LCD MONITOR

Type	7.5 cm (3.0") Touchscreen LCD (TFT). 3:2 aspect ratio. Approx. 1,040,000 dots. Electrostatic capacitive type. Vari-Angle
------	--

## Coverage

Brightness Adjustment	Approx 100%
-----------------------	-------------

## Display Options

Adjustable to one of seven levels  
Customisable and toggle via INFO. Button  
(1) Liveview image with exposure info  
(2) Liveview image with basic info  
(3) Liveview image with full info

Customisable settings:  
Grid overlay (x3 formats), Histogram (Brightness/ RGB), Electronic Level, Multi aspect ratios, Hints and Tips

## FLASH

### Built-in Flash GN (ISO 100, meters)

5

### Built-in Flash Coverage

Maximum coverage at approx. 15mm (35mm equivalent: approx. 24mm)

### Built-in Flash recycle time

Approx. 3 seconds <sup>[27]</sup>



# TECHNICAL SPECIFICATIONS

# EOS M50

<b>Modes</b>	Auto (E-TTL II)	<b>Movie Length</b>	Max duration 29min 59sec, Max file size 4GB
<b>Red-Eye Reduction</b>	Yes - with red eye reduction lamp	<b>Folders</b>	New folders can be created and selected
<b>X-sync</b>	1/200 sec	<b>File Numbering</b>	(1) Continuous, Auto Reset (2) Manual Reset
<b>Flash Exposure Compensation</b>	+/- 2 EV in 1/3 increments	<b>OTHER FEATURES</b>	
<b>Flash Exposure Lock</b>	Yes	<b>Custom Functions</b>	9 customisable buttons
<b>Second Curtain Synchronisation</b>	Yes	<b>Metadata Tag</b>	User copyright information (Author's Name, Copyright Details) Image rating (0-5 stars)
<b>HotShoe/ PC terminal</b>	Yes/No	<b>Playback zoom</b>	15 steps plus smooth pinch-to-zoom
<b>External Flash Compatibility</b>	E-TTL II with EX series Speedlites, wireless multi-flash support	<b>Display Formats</b>	(1) Single image with information (toggle options) (2) Single image (3) Index display (4/9/36/100 images) (4) Jump Display (1/10/custom number image, by shot date, by rating, by folder, by movies only, protected only)
<b>External Flash Control</b>	Via camera setting/ flash setting menu	<b>Slide Show</b>	Playback time: 1/2/3/5/10/30 seconds Repeat: On/Off Transition Effects: Off, Slide in 1-2, Fade 1-3 Brightness/ RGB
<b>SHOOTING</b>		<b>Histogram</b>	Yes
<b>Modes</b>	Scene Intelligent Auto, Hybrid Auto, Creative Assist, SCN(Self-Portrait, Portrait, Smooth Skin, Landscape, Sports, Close-up, Food, Panning, Handheld Night Scene, HDR Backlight Control, Silent Mode), Creative Filters (Grainy B/W, Soft Focus, Fish-eye Effect, Water painting effect, Toy camera effect, Miniature effect , HDR Art standard, vivid, bold, embossed), Program AE , Shutter priority AE, Aperture priority AE, Manual exposure, Movie (Movie auto exposure, Movie manual exposure, Time-lapse movie)	<b>Highlight Alert</b>	Yes
<b>Picture Styles</b>	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)	<b>Image Erase/Protection</b>	Erase: Single image, Selected images, Selected range, All images Protection: Selected images, Selected range, All images, Unprotect all images
<b>Colour Space</b>	sRGB and Adobe RGB	<b>Menu Categories</b>	(1) Shooting menu (x8) (2) Playback menu (x4) (3) Setup menu (x5) (4) Display menu (5) My Menu
<b>Image Processing</b>	Highlight Tone Priority (standard and enhanced) Auto Lighting Optimizer (4 settings) Long exposure noise reduction High ISO speed noise reduction (4 settings + Multi Shot NR) Lens peripheral illumination correction Chromatic aberration correction Diffraction correction	<b>Menu Languages</b>	29 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Vietnamese, Indonesian, Hindi, Japanese
	Creative Assist: Presets Background Blur (5 settings) Brightness (19 levels) Contrast (9 levels) Saturation (9 levels) Color Tone 1 & 2 (19 levels) Monochrome (Off/Black and white/Sepia/Blue/Purple/Green)	<b>Firmware Update</b>	Firmware update possible by the user.
<b>Drive modes</b>	Single, High-Speed Continuous, Low-Speed Continuous, Self timer (2s, 10s, Custom, Remote)	<b>INTERFACE</b>	
<b>Continuous Shooting</b>	One shot AF: Approx. 10 shots/sec for up to 33 frames in JPEG and 10 frames in RAW <sup>[21]</sup>  With Servo AF: Approx. 7.4 shots/sec for up to approx 47 frames in JPEG <sup>[22]</sup>	<b>Computer</b>	Hi-Speed USB (Micro USB) Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only, 1-11 ch), with Dynamic NFC support <sup>[17]</sup>
		<b>Other</b>	Bluetooth® (Specification version 4.1, Bluetooth low energy technology) <sup>[23] [25]</sup>  HDMI (Micro - Type-D connector), HDR output to compatible TV supported
<b>LIVE VIEW MODE</b>		<b>DIRECT PRINT</b>	
<b>Coverage</b>	Approx. 100% (horizontally and vertically)	<b>Canon Printers</b>	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
<b>FILE TYPE</b>		<b>PictBridge</b>	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
<b>Still Image Type</b>	JPEG: Fine, Normal (Exif 2.31 compliant) / Design rule for Camera File system (2.0) RAW: RAW (CR3 14-bit), Digital Print Order Format [DPOF] Version 1.1 compliant	<b>STORAGE</b>	
<b>RAW+JPEG simultaneous recording</b>	Yes, RAW + various JPEG compression possible	<b>Type</b>	SD, SDHC, SDXC (UHS-I compatible)
<b>Image Size</b>	RAW: [3:2] 6000 x 4000, [4:3] 5328 x 4000, [16:9] 6000 x 3368, [1:1] 4000 x 4000  JPEG 3:2: (L) 6000 x 4000, (M) 3984 x 2656, (S1) 2976 x 1984, (S2) 2400 x 1600 JPEG 4:3: (L) 5328 x 4000, (M) 3552 x 2664, (S1) 2656 x 1992, (S2) 2112 x 1600 JPEG 16:9: (L) 6000 x 3368, (M) 3984 x 2240, (S1) 2976 x 1680 (S2) 2400 x 1344 JPEG 1:1: (L) 4000 x 4000, (M) 2656 x 2656, (S1) 1984 x 1984, (S2) 1600 x 1600	<b>SUPPORTED OPERATING SYSTEM</b>	Windows 10 / 8.1 / 8 / 7 SP1 <sup>[24]</sup> Mac OS X 10.9 / 10.10 / 10.11 / 10.12
<b>Movie Type</b>	In-camera RAW processing & Image Resize available in playback MP4 [Video: MPEG-4 AVC/H.264, Audio: MPEG-4 AAC-LC (stereo)]	<b>PC &amp; Macintosh</b>	For Wi-Fi connection to a PC: Windows 10 / 8.1 / 8 / 7 SP1 Mac OS X 10.9 / 10.10
<b>Movie Size</b>	4K - 3840 x 2160 (23.98, 25 fps) Full HD - 1920 x 1080 (59.94, 50, 29.97, 25, 23.976 fps) HD - 1280 x 720 (119.9, 100, 59.94, 50 fps)	<b>SOFTWARE</b>	For Image Transfer Utility: Windows 10 / 8.1 / 8 / 7 SP1 Mac OS X 10.9 / 10.10 / 10.11 / 10.12
		<b>Image Processing</b>	Digital Photo Professional Picture Style Editor, EOS Utility, Image Transfer Utility
		<b>Other</b>	Camera Connect app available on iOS and Android devices <sup>[25]</sup>

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS M50

## POWER SOURCE

### Batteries

#### Battery life

1 x Rechargeable Li-ion Battery LP-E12  
 Approx. 235 shots (at 23°C, AE 50%, FE 50%)<sup>[5]</sup>  
 Eco Mode: Approx. 370 shots  
 Movie Recording: Approx. 85 mins  
 Playback time when playing back a slideshow of still images: Approx. 4 hrs

### Battery Indicator

#### Power saving

4 levels  
 Display off (15, 30 sec or 1, 3, 5, 10, 30 mins)  
 Auto Power Down (30 sec or 1, 3, 5, 10 mins, Disable)  
 Viewfinder off (1, 3 min, disable)  
 ECO mode

### Power Supply & Battery Chargers

Battery charger LC-E12E  
 Compact Power Adapter CA-PS700  
 DC Coupler DR-E12

## PHYSICAL SPECIFICATIONS

### Body Materials

Polycarbonate

### Operating Environment

0 – 40 °C, 85% or less humidity

### Dimensions (WxHxD)

116.3 x 88.1 x 58.7mm

### Weight (body only)

Approx 387g (black), 390g (white), CIPA testing standard including battery and memory card

## ACCESSORIES

### Cases / Straps

Body Jacket EH32-CJ (beige)  
 Body Jacket EH32-CJ (light brown)  
 Neck Strap EM-E2 (black)  
 Neck Strap EM-E2 (white)  
 Neck Strap EM-200DB

### Lenses

EF-M lenses  
 All EF and EF-S lenses compatible via Mount adapter EF-EOS M

### Flash

Canon Speedlites (including 90EX, 220EX, 270EX, 270EX II, 320EX, 380EX, 420EX, 430EX, 430EX II, 430EX III, 430EX III-RT, 550EX, 580EX, 580EX II, 600EX, 600EX-RT, 600EX II-RT, Macro-Ring-Lite, MR-14EX II, Macro Twin Lite MT-24EX, Speedlite Transmitter ST-E2, Speedlite Transmitter ST-E3-RT)

### Remote Controller/ Switch

Off-Camera Shoe Cord OC-E3, Speedlite Bracket SB-E2

### Other

Bluetooth Remote BR-E1  
 Interface cable IFC-400PCU  
 Mount Adapter EF-EOSM

All data is based on Canon standard testing methods except where indicated. Subject to change without notice. -

<sup>[1]</sup> Large/Fine(Quality 8) resolution

<sup>[2]</sup> Based on Canon's testing conditions, JPEG, ISO 100, Standard Picture Style. Varies depending on the subject, memory card brand and capacity, image recording quality, ISO speed, drive mode, Picture Style, Custom functions etc.

<sup>[3]</sup> Compatible with large memory card capacities, including cards of 2GB and more (camera may require firmware update).

<sup>[4]</sup> with 50mm lens at infinity, -1m<sup>-1</sup> dpt

<sup>[5]</sup> Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated

<sup>[6]</sup> Memory card and battery door only

<sup>[7]</sup> with EF300mm f/2.8L IS USM at 50kph

<sup>[8]</sup> Recommended Exposure Index

<sup>[9]</sup> Environmental protection

<sup>[10]</sup> Maximum fps and buffer capacity may be reduced depending on the cameras settings and light level

<sup>[11]</sup> Peripheral Cross type AF points will not function as a cross type AF points with the following lenses: EF 35-80mm f4.5-5.6 (II/III/USM), EF35-105mm f4.5-5.6 (USM), EF 80-200mm f4.5-5.6 (II)

<sup>[12]</sup> With Battery strength 75% or higher

<sup>[13]</sup> Viewfinder Information

<sup>[14]</sup> Hybrid CMOS AF III covers an area of approx. 80% Vertical x 70% Horizontal of the frame

<sup>[15]</sup> Maximum number of AF frame is dependent on selected image aspect ratio

<sup>[16]</sup> Sustained continuous shooting function requires compatible SDHC/SDXC UHS Speed Class 1 memory card, total number of frames captured varies depending on camera settings, type of lens used, battery charge and light level. Shooting stops automatically with the 1000th frame

<sup>[17]</sup> Wi-Fi use may be restricted in certain countries or regions.

<sup>[18]</sup> Hybrid CMOS AF II covers an area of approx. 80% Vertical x 70% Horizontal of the frame

<sup>[19]</sup> Maximum burst during continuous shooting are measured based on Canon's testing standards (3:2 aspect ratio, ISO 200 and Standard Picture Style)

<sup>[20]</sup> Dual Pixel CMOS AF - AF is possible over an area of approx. 80% Vertical x 80% Horizontal of the frame

<sup>[21]</sup> Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Total number of frames captured and continuous shooting speed may vary depending on camera exposure settings, type of lens used, battery level, light level and memory card used.

<sup>[22]</sup> Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Under Servo AF, maximum continuous shooting speed and total number of frames captured depends on subject condition, camera settings and lens used

<sup>[23]</sup> Equipped with Bluetooth<sup>®</sup> low energy technology. The Bluetooth<sup>®</sup> word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Canon Europe Ltd. is under license. Other trademarks and trade names are those of their respective owners.

<sup>[24]</sup> Software applications compatible with Windows 10 in Windows 10 Desktop Mode only

<sup>[25]</sup> Bluetooth functionality with Camera Connect app requires smart device to be equipped with Bluetooth version 4.0 (or later). Also requires smart device to be using operating system iOS 8.4 (or later) or Android 5.0 (or later)

<sup>[26]</sup> Require Remote Controller Adapter RA-E3

<sup>[27]</sup> When battery is fully charged

<sup>[28]</sup> Maximum continuous shooting speed with 1/500 sec. or faster shutter speed,



# DO YOUR STORIES JUSTICE

# EOS M50

A sleek design classic, this mirrorless camera will inspire you to make memorable stories you'll be proud to share thanks to technologies like 4k movies, a DSLR sized sensor and effortless connectivity.

Sales Start Date: April 2018 (TBC)



#### PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
D.CAMERA EOS M50 BK BODY EU26	2680C002AA	4549292109412
D.CAMERA EOS M50 WH BODY EU26	2681C002AA	4549292109528
D.CAMERA EOS M50 BK M15-45 S EU26	2680C012AA	4549292108910
D.CAMERA EOS M50 WH M15-45 S EU26	2681C012AA	4549292109177
D.CAMERA EOS M50 BK M15-45 S + M55-200 EU26	2680C022AA	4549292109009
D.CAMERA EOS M50 WH M15-45 S + M55-200 EU26	2681C022AA	4549292109320
D.CAMERA EOS M50 BK M15-45 S + M22 EU26	2680C032AA	4549292109467
D.CAMERA EOS M50 WH M15-45 S + M22 EU26	2681C032AA	4549292109566
D.CAMERA EOS M50 BK M18-150 EU26	2680C042AA	4549292109498
D.CAMERA EOS M50 WH M18-150 EU26	2681C042AA	4549292109580

#### OPTIONAL ACCESSORIES:

Product Name	Mercury Code	EAN Code
Body Jacket EH32-CJ (Beige)	2685C001AA	4549292109764
Body Jacket EH32-CJ (Light Brown)	2686C001AA	4549292109788

The Canon logo is displayed in its signature red font.

Live for the story\_

# DO YOUR STORIES JUSTICE

# EOS M50

A sleek design classic, this mirrorless camera will inspire you to make memorable stories you'll be proud to share thanks to technologies like 4k movies, a DSLR sized sensor and effortless connectivity.



## MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
D.CAMERA EOS M50 BK BODY EU26	2680C002AA	EA	Each	1	16.75	16.75	13.7	0.9
		CT	Carton	6	42.95	35.5	20.55	6.35
		EP	Euro Pallet	150	120	80	118	169
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAMERA EOS M50 WH BODY EU26	2681C002AA	EA	Each	1	16.75	16.75	13.7	0.85
		CT	Carton	6	42.95	35.5	20.55	6.09
		EP	Euro Pallet	150	120	80	118	162
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAMERA EOS M50 BK M15-45 S EU26	2680C012AA	EA	Each	1	16.75	16.75	13.7	1.047
		CT	Carton	6	42.95	35.5	20.55	7.29
		EP	Euro Pallet	150	120	80	118	192
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAMERA EOS M50 WH M15-45 S EU26	2681C012AA	EA	Each	1	16.75	16.75	13.7	1.052
		CT	Carton	6	42.95	35.5	20.55	7.32
		EP	Euro Pallet	150	120	80	118	193
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAMERA EOS M50 BK M15-45 S + M55-200 EU26	2680C022AA	EA	Each	1	16.75	21.35	13.7	1.365
		CT	Carton	6	43	35.5	25.2	9.21
		EP	Euro Pallet	120	120	80	115.8	194
			Layers per Pallet	4				
			Cartons per Layer	5				
			Products per layer	24				

Live for the story\_

# DO YOUR STORIES JUSTICE

# EOS M50

A sleek design classic, this mirrorless camera will inspire you to make memorable stories you'll be proud to share thanks to technologies like 4k movies, a DSLR sized sensor and effortless connectivity.



## MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
D.CAMERA EOS M50 WH M15-45 S + M55-200 EU26	2681C022AA	EA	Each	1	16.75	21.35	13.7	1.370
		CT	Carton	6	43	35.5	25.2	9.24
		EP	Euro Pallet	120	120	80	115.8	195
			Layers per Pallet	4				
			Cartons per Layer	5				
			Products per layer	24				
D.CAMERA EOS M50 BK M15-45 S + M22 EU26	2680C032AA	EA	Each	1	16.75	16.75	13.7	1.333
		CT	Carton	6	42.95	35.5	20.55	9.00
		EP	Euro Pallet	150	120	80	118	235
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAMERA EOS M50 WH M15-45 S + M22 EU26	2681C032AA	EA	Each	1	16.75	16.75	13.7	1.338
		CT	Carton	6	42.95	35.5	20.55	9.03
		EP	Euro Pallet	150	120	80	118	236
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAMERA EOS M50 BK M18-150 EU26	2680C042AA	EA	Each	1	16.75	16.75	13.7	1.216
		CT	Carton	6	42.95	35.5	20.55	8.30
		EP	Euro Pallet	150	120	80	118	218
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAMERA EOS M50 WH M18-150 EU26	2681C042AA	EA	Each	1	16.75	16.75	13.7	1.221
		CT	Carton	6	42.95	35.5	20.55	8.33
		EP	Euro Pallet	150	120	80	118	218
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				

Live for the story\_

# DO YOUR STORIES JUSTICE

# EOS M50

A sleek design classic, this mirrorless camera will inspire you to make memorable stories you'll be proud to share thanks to technologies like 4k movies, a DSLR sized sensor and effortless connectivity.



## MEASUREMENT / LOGISTIC INFORMATION (ACCESSORIES) :

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
Body Jacket EH32-CJ (Beige)	2685C001AA	EA	Each	1	5.5	12.5	6.94	0.05
		CT	Carton	40	27.7	30.9	33.4	2.62
		EP	Euro Pallet	TBC	120	80	TBC	TBC
			Layers per Pallet	TBC				
			Cartons per Layer	TBC				
			Products per layer	TBC				
Body Jacket EH32-CJ (Light Brown)	2686C001AA	EA	Each	1	5.5	12.5	6.94	0.05
		CT	Carton	40	27.7	30.9	33.4	2.62
		EP	Euro Pallet	TBC	120	80	TBC	TBC
			Layers per Pallet	TBC				
			Cartons per Layer	TBC				
			Products per layer	TBC				

## What's in the box?

### EOS M50 BK M15-45 S+ EF50 f/1.8 S + Mount Adapter EU26

- Digital Camera EOS M50 body
- Battery Charger LC-E12E
- Battery Pack LP-12
- Camera Cover R-F-4
- Lens EF-M15-45 S f/3.5-6.3 IS STM
- Lens Cap E-49
- Lens Dust Cap EB
- Lens EF50mm f/1.8 STM
- Lens Cap E-49
- Lens Dust Cap E
- Camera Mount Adapter EF-EOS M
- Power Cable
- Strap EM-200DB
- User Manual Kit

### EOS M50 BK M15-45 S + SB130 + 16GB EU26

- Digital Camera EOS M50 body
- Battery Charger LC-E12E
- Battery Pack LP-12
- Camera Cover R-F-4
- Lens Cap E-49
- Lens Dust Cap EB
- Lens EF-M15-45 S f/3.5-6.3 IS STM
- Power Cable
- Strap EM-200DB
- User Manual Kit
- Shoulder Bag CB-SB130 Black
- SD Card 16GB Class 10
- Lens Cleaning Cloth

Live for the story\_



# DO YOUR STORIES JUSTICE

# EOS M50

A sleek design classic, this mirrorless camera will inspire you to make memorable stories you'll be proud to share thanks to technologies like 4k movies, a DSLR sized sensor and effortless connectivity.



## What's in the box?

### EOS M50 Body only

- Digital Camera EOS M50 body
- Camera Cover R-F-4
- Strap EM-200DB
- Battery Charger LC-E12E
- AC Cable
- Battery Pack LP-E12
- User Manual Kit

### EOS M50 + EF-M15-45 S

- Digital Camera EOS M50 body
- Camera Cover R-F-4
- EF-M15-45 S f/3.5-6.3 IS STM
- Lens Cap E-49
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- AC Cable
- Battery Pack LP-E12
- User Manual Kit

### EOS M50 + EF-M15-45 S + EF-M55-200

- Digital Camera EOS M50 body
- Camera Cover R-F-4
- EF-M15-45 S f/3.5-6.3 IS STM
- Lens Cap E-49
- EF-M55-200mm f/4.5-6.3 IS STM
- Lens Cap E-52 II
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- AC Cable
- Battery Pack LP-E12
- User Manual Kit

### EOS M50 + EF-M15-45 S + EF-M22

- Digital Camera EOS M50 body
- Camera Cover R-F-4
- EF-M15-45 S f/3.5-6.3 IS STM
- Lens Cap E-49
- EF-M 22mm f/2 STM
- Lens Cap E-43
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- AC Cable
- Battery Pack LP-E12
- User Manual Kit

### EOS M50 + EF-M18-150 S

- Digital Camera EOS M50 body
- Camera Cover R-F-4
- EF-M18-150mm f/3.5-6.3 IS STM
- Lens Cap E-55
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- AC Cable
- Battery Pack LP-E12
- User Manual Kit

**Canon**

Live for the story\_

# EOS M50

## DO YOUR STORIES JUSTICE



- Modern, hassle free shooting for superb results
- Compact, sleek and intuitive shooting experience
- Clever connectivity and control with Wi-Fi\* & Bluetooth\*\*
- Inspiring technologies for stories you'll be proud of
- Creative freedom to capture every story

\*Wi-Fi: Not all functions or devices are supported; see full specifications for details.

\*\*Equipped with Bluetooth® low energy technology. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Canon Inc. is under license. Other trademarks and trade names are those of their respective owners. Initial pairing with compatible device required.

A sleek design classic, this mirrorless camera will inspire you to make memorable stories you'll be proud to share thanks to technologies like 4k movies, a DSLR sized sensor and effortless connectivity.

**24.1** MEGA  
PIXELS  
CMOS



**Dual Pixel AF**  
CMOS

**10**  
Frames  
Per Sec



**OLED EVF**  
2,360k dots

### Price:

€ 679 EOS M50 BODY EU26  
€ 799 EOS M50 M15-45 EU26  
€ 1029 EOS M50 M15-45+200 EU26  
€ 949 EOS M50 M15-45+M22 EU26  
€ 1049 EOS M50 M18-150 EU26

**Embargo Date:** 26<sup>th</sup> February 2018

**Sales Start Date:** April 2018 (TBC)

**Key Sales Channel**

### Competition

Sony a6300, Fujifilm X-T20,  
Panasonic G7,  
Olympus OM-D E-M10 III

### Customer and Positioning

Max, Adventurous Achiever.  
Combination of cutting edge tech never seen at this price point whilst still looking and feeling modern and cool

### Launch Promotion

**Canon**

Live for the story\_