

# SINGLE-FUNCTION BLACK & WHITE PRINTER OFFERING RELIABILITY AND GREATER COST CONTROL.

The i-SENSYS LBP210 series are fast, double sided, A4 black and white printers engineered to enhance work flow and productivity, and cut costs. Delivering improved, high-quality results, they are ideal for SMEs.



LBP212dw



LBP214dw



LBP215x

- Save time with fast print speeds of up to 38ppm (LBP214dw/ LBP215x)
- High quality 1200 x 1200 dpi print resolution
- Easy operation with large colour touchscreen on LBP215x
- Compatible with AirPrint and Mopria for mobile connectivity
- Large storage with 1GB internal memory
- Secure PIN printing from mobile devices (LBP214dw/ LBP215x)
- Improved flexibility with varied media support; A4, A5,A6
- Quick and simple mobile connectivity via QR code (LBP215x)
- Application Library allowing automation, added shortcuts and a customised interface(LBP215x)
- Universal Login Manager function and uniFLOW ready (LBP215x)

## OPTIONAL ACCESSORIES

### Cassette Feeding Module AH1

- Additional 550 sheet paper cassette, 1unit can be added to main unit.

### Barcode Print Kit- E1E (Available on LBP215x)

- Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation.

## TECHNICAL SPECIFICATIONS

### PRINTER ENGINE

<b>Print speed</b>	LBP214dw, LBP215x Single sided : Up to 38 ppm (A4) Up to 63.1 ppm(A5-Landscape) Double sided : Up to 30.3 ipm (A4) LBP212dw Single sided : Up to 33 ppm (A4) Up to 52.5 ppm(A5-Landscape) Double sided : Up to 26.4 ipm (A4)
<b>Printing method</b>	Monochrome laser beam printing
<b>Print quality</b>	Up to 1200 x 1200 dpi
<b>Print resolution</b>	600 x 600 dpi
<b>Warm-up time</b>	Approx. 14 seconds or less from power on
<b>First Page Out Time</b>	Approx: 5.5 seconds or less
<b>Recommended Monthly Print Volume</b>	750 - 4,000 pages per month
<b>Duty cycle</b>	80,000 pages
<b>Print margins</b>	5 mm-top, bottom, left and right
<b>Advanced printing features</b>	Secure Print (LBP214dw, LBP215x only) Print from USB memory key (JPEG/TIFF/PDF) Barcode Print <sup>1</sup> (LBP215x only) Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app

### MEDIA HANDLING

<b>Paper input (Standard)</b>	250-sheet cassette 100-sheet multi-purpose tray
<b>Paper input (Option)</b>	550-sheet cassette
<b>Paper output</b>	150-sheet
<b>Media types</b>	Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope
<b>Media sizes</b>	Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COMIO, Monarch, C5, DL), Custom sizes: Min. 105 x 148 mm Max. 215.9 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COMIO, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm.
<b>Media weights</b>	Cassette (standard and optional): 52 to 120 g/m <sup>2</sup> multi-purpose tray: 52 to 163 g/m <sup>2</sup>
<b>Double sided printing</b>	A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap Custom size - Min. 210 x 279.4 mm Max. 215.9 x 355.6 mm 60 to 120 g/m <sup>2</sup>

### GENERAL FEATURES

<b>Power requirements</b>	220-240V(±10%) 50/60Hz (±2Hz)
<b>Power consumption</b>	Maximum: Approx. 1,300 W Standby: Approx. 10 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): LBP215x/214dw 1.2 kWh/week (230V) LBP212dw 1.1 kWh/week(230V) For detailed information relating to Lot26 regulation, please go to: <a href="http://www.canon-europe.com/For_Work/Lot26/index.aspx">http://www.canon-europe.com/For_Work/Lot26/index.aspx</a>
<b>Noise level</b>	Sound Pressure <sup>2</sup> : Active: 56 dB Standby: Inaudible <sup>3</sup> Sound Power <sup>2</sup> : Active: 72.2 dB Standby: Inaudible <sup>3</sup>

### Dimensions (W x D x H)

LBP215x: 438 mm x 373 mm x 312 mm  
LBP214dw/LBP212dw: 401 mm x 373 mm x 250 mm

### Weight

LBP215x: Approx. 9.9 Kg  
LBP214dw/LBP212dw: Approx. 9.5 Kg

### Operating environment

Temperature: 10 to 30°C (50 to 86°F)  
Humidity 20 to 80% RH (no condensation)

### Control panel

LBP215x: 12.7 cm LCD Colour Touch Screen  
LBP214dw/LBP212dw: 5 Line LCD, 3 LED (Job, Error, Energy saver), Buttons, 10-key numeric keypad

### CONTROLLER

**Processor Speed** 800MHz x 2

**Memory** 1GB

**Printer Languages** LBP215x/LBP214dw: UFRII, PCL 5e<sup>4</sup>, PCL6, Adobe<sup>®</sup> PostScript  
LBP212dw: UFRII, PCL 5e<sup>4</sup>, PCL6

### Fonts

LBP215x: 93 PCL fonts, 136 PS fonts  
LBP214dw/LBP212dw: 45 PCL fonts, 136 PS fonts

### Interface and connectivity

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

### Software and Printer Management

Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Management Console: Server-based software for centralised management of a fleet of devices  
eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.  
Universal Log-in Manager (LBP215x only)  
uniFLOW online (LBP215x only)  
uniFLOW online Express (LBP215x only)  
uniFLOW Compatibility with embedded uniFLOW Login Device Client (LBP215x only)

Windows<sup>®</sup> 10 / Windows<sup>®</sup> 8.1 / Windows<sup>®</sup> 7 / Server<sup>®</sup> 2016 / Server<sup>®</sup> 2012R2 / Server<sup>®</sup> 2012 / Server<sup>®</sup> 2008R2 / Server<sup>®</sup> 2008  
Mac OS X version 10.8.5 & up  
Linux<sup>5</sup>

### CONSUMABLES

**All-in-One cartridges** Cartridge 052 (3,100 pages<sup>6</sup>)<sup>7</sup>  
Cartridge 052H (9,200 pages<sup>6</sup>)<sup>7</sup>

### ACCESSORIES/ OPTIONS

**Items** Cassette Feeding Module-AH1  
MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) (LBP215x only)  
MiCard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW) (LBP215x only)  
MiCard Attachment kit-B1 (LBP215x only)  
Barcode Printing Kit-E1E (LBP215x only)

### Notes:

<sup>1</sup>Accessory - Barcode Printing Kit-E1E - is required

<sup>2</sup>Declared noise emission in accordance with ISO 9296

<sup>3</sup>Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

<sup>4</sup>A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

<sup>5</sup>Web distribution only  
Available from December 2018.

<sup>6</sup>Based on ISO/IEC 19752

<sup>7</sup>Printer ships with starter cartridge (Black: 1,600pages)

# SINGLE-FUNCTION BLACK & WHITE PRINTER OFFERING RELIABILITY AND GREATER COST CONTROL.

i-SENSYS LBP212dw \\  
LBP214dw \ LBP215x

The i-SENSYS LBP210 series are fast, double sided, A4 black and white printers engineered to enhance work flow and productivity, and cut costs. Delivering improved, high-quality results, they are ideal for SMEs.

Sales Start Date: April 2018



## PRODUCT DETAILS:

Product name	Mercury code	EAN Code
i-SENSYS LBP212dw	2221C006AA	4549292090208
i-SENSYS LBP214dw	2221C005AA	4549292090192
i-SENSYS LBP215x	2221C004AA	4549292090185

## ACCESSORIES:

Product name	Mercury code	EAN Code
Cassette Feeding Module-AH1	0732A033AA	4549292092769
MiCard Attachment kit-B1	5146B002AA	4549292027235
Barcode Printing Kit-E1E	5143B002AA	N/A (e-delivery)

## CONSUMABLES:

Product name	Mercury code	EAN Code
Cartridge 052	2199C002AA	4549292089400
Cartridge 052 H	2200C002AA	4549292089424

## EASY SERVICE PLAN:

Product Name	Mercury Code	EAN Code
Installation service	7950A546AA	4960999794426
3-year on-site next day service-Pack A (LBP212dw & LBP214dw)	7950A525AA	4960999793290
3-year on-site next day service-Pack B (LBP215x)	7950A526AA	4960999793306