

# XA55 / XA50

## A 1.0-TYPE CMOS SENSOR COMPACT 4K CAMCORDER WITH DUAL PIXEL CMOS AF AND 15X ZOOM LENS

The highly compact and lightweight XA55 / XA50 offers high quality 4K UHD image quality with beneficial features such as Dual Pixel CMOS AF, Canon 15x optical zoom lens and advanced Full HD image quality driven by utilising outstanding Over Sampling HD Processing.



- 1.0-type CMOS sensor
- High quality 4K 15x optical zoom lens
- Fast and precise Dual Pixel CMOS AF
- XF-AVC and MP4 recording to SD cards
- Compact and lightweight with professional functions
- 3G-SDI interface (XA55 Only)



Dual Pixel CMOS AF

OPTICAL IMAGE STABILIZER DYNAMIC

Over Sampling HD Processing

### PRODUCT RANGE



XA55 / XA50 (4K UHD)



XA40 (4K UHD)



XA15 / XA11 (Full HD)

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# XA55 / XA50

## CAMERA

### IMAGE SENSOR

**Sensor**  
**Filter**  
**Total pixels**  
**Effective pixels per sensor**  
**Subject illumination range**  
**Minimum illumination (PAL)**

1.0-type CMOS  
 RGB Primary Colour Filter  
 Approx. 13.4 MP  
 Approx. 8.29 MP (3840 x 2160)  
 Approx. 0.1 lx to 100,000 lx  
 P Mode: Approx. 1.4 lx (shutter speed 1/25 sec., 50.00P; with auto slow shutter On)  
 Low Light Mode: Approx. 0.1 lx (shutter speed 1/2 sec.)

### LENS

**Zoom ratio**  
**Focal length (35mm equivalent)**  
**Minimum focus distance**  
**Aperture**  
**Aperture blades**  
**Filter diameter**  
**Image stabilization system**

15x optical  
 Approx. 25.5 to 382.5 mm Standard IS/IS Off  
 10 mm at wide end, 60 cm across entire zooming range  
 f/2.8 - f/11 (AV Priority and Manual Modes)  
 9 blades  
 58mm  
 Optical system (lens shift) + electronic stabilization  
 Dynamic, Standard, Powered, Off

### ND filter

3 densities: turret switched, motor-driven.  
 ND 1/4, ND 1/16, and ND 1/64.

### Zoom control

Zoom rockers on body and handle;  
 Selectable manual zoom/focus ring on lens;  
 Wireless controller;  
 Selectable High Speed mode available.

### Zoom speed

Variable (body rocker only) or Constant speed (body rocker, handle rocker and wireless controller;  
 Fast/Normal/Slow, 16 speed level settings in each)

### Focus control

MANUAL: Lens ring and touchscreen point selection (Focus Guide and Peaking assist functions), Focus Preset.  
 AUTOFOCUS: Touchscreen AF point selection, Face Detection and Tracking, Face Only AF.  
 (Continuous AF, AF-Boosted MF, AF Speed, AF Response, AF Frame size)

### Focus System

Dual Pixel CMOS AF, Contrast AF

### Iris control

Touchscreen, Auto

### Digital zoom/Teleconverter

300x Digital Zoom, 2x Digital Teleconverter

## IMAGE PROCESSOR

### Type

DIGIC DV6

### Dynamic range

800% in Wide DR mode

### Colour sampling

YCC 4:2:0

### Bit depth

8-bit

## RECORDING

### Video storage media

SD/SDHC/SDXC card (2 card slots)

### Type

Class U3 cards recommended

### Recording time (64GB Card, approx.)

MP4: 150Mbps: 55 mins / 35Mbps: 220 mins  
 XF-AVC: 160 Mbps: 50 mins / 45 Mbps: 185 mins

### Recording file system

FAT32/exFAT

### Internal recording format (PAL)

XF-AVC: 3840 x 2160 (160Mbps) / 1920 x 1080 (45 Mbps)  
 MP4: 3840 x 2160 (150Mbps) / 1920 x 1080 (35/17 Mbps)

### External recording output (PAL)

SDI\* / HDMI output (Camera mode)  
 UHD recording mode: 1920 x 1080 25.00P YCC4:2:2 8-bit  
 Full HD recording mode: 1920 x 1080 50.00P/25.00P; 1280 x 720 50.00P YCC4:2:2 10-bit

\* SDI output with XA55 only

### External monitoring

SDI\* / HDMI (50.00i)  
 \* SDI output with XA55 only

### Recording frame rate (PAL)

MP4: 25.00P (UHD), 50.00P/25.00P (Full HD)  
 XF-AVC: 25.00P (UHD), 50.00P/50.00i/25.00P (Full HD)

### Slow/Fast motion (PAL)

3840 x 2160 / 25.00P: x2, x4, x10, x20, x60, x120, x600, x1200  
 1920 x 1080 / 50.00P: x2, x4, x10, x20, x60, x120, x600, x1200  
 1920 x 1080 / 25.00P: x0.5

### Pre Recording function

Yes, 3 seconds

### Still photos

JPEG up to 3840x2160  
 (Still image resolution is dependent on the video resolution)  
 SD Card

### Photo storage media

## AUDIO

### Recording

MP4: MPEG-2 AAC-LC (16-bit 2ch) / LPCM (16-bit 4ch)  
 XF-AVC: LPCM (24-bit 4ch)

### Audio control

Manual or Auto  
 Independent 2ch Line/Mic/Mic+48V input;  
 Independent level control per channel (-∞ to +18 dB);  
 Independent audio limiters (2 ch);  
 Input mic trimming

### Reference tone

1KHz, -12dB / -18dB / -20dB / Off

### Microphone attenuation

On/Off (20dB)

### Microphone level meter

Yes

## SYSTEM

### MONITORING PANEL

#### Type

Capacitive LCD touch panel

#### Size

3.0-inch (7.5 cm, approx. 460,000 dots)

#### Waveform Monitor

No

#### Focus Assist

Dual Pixel Focus Guide / Peaking / Magnify

#### Peaking

Selectable Peaking Colour: Red / Blue / Yellow

#### Zebra

70% or 100% reference level

#### Markers

Grid (white/grey) and Level (white/grey)

## VIEWFINDER

### Size

0.24-inch, approx. 1.56 million dots

### Correction lens

+2.0 to -5 dioptre

## INPUTS/OUTPUTS

### Audio input

XLR 3-pin jack (x2) with 48V phantom power, Line and Mic options on detachable handle,  
 3.5mm microphone input jack (Supply Voltage 2.4V DC), Built-in Mic

### Headphone output

3.5mm stereo mini jack

### HDMI output

HDMI™ mini connector

### USB

Min-B, Hi-Speed USB, PTP class supported

### SDI output

XA55: 3G-SDI with BNC connector

XA50: No

### Time code

Superimposed on HDMI output signal (Camera Mode only)

### Genlock

No

### LAN

No

### AV terminal

No

### DC input

3.4mm jack

### Remote Control Terminal

2.5mm mini jack

Live for the story\_

# TECHNICAL SPECIFICATIONS

# XA55 / XA50

<b>SHOOTING FUNCTIONS</b>		<b>TIME CODE</b>	
<b>EXPOSURE</b>		<b>Count up system</b>	Regen / Rec Run / Free Run / Preset (Non-Drop Frame)
<b>Exposure metering</b>	Centre-weighted average or segment evaluative (determined by shooting mode) No metering: Fireworks mode, Fixed exposure (1/50 sec.)	<b>Time Code out</b>	Via HDMI out. Superimposed on output, Camera Mode only
<b>Exposure compensation</b>	Highlight AE, Exposure lock, Auto backlight compensation, Exposure compensation amount shown as $\pm 3$ when locked or $\pm 2$ in AUTO ( $\pm 8$ increments).	<b>ACCESSORIES</b>	
<b>Exposure Lock</b>	Yes.	<b>Supplied</b>	Lens hood with barrier, Mic holder unit, Handle Unit HDU-3, Wireless Controller WL-D89, Lithium battery (CR2025), Compact Power Adapter CA-570, Battery Pack BP-820, AC Cable, Lens Cap
<b>Auto Gain Control setting</b>	Auto / Manual	<b>Optional (Includes items not currently on sale)</b>	Canon Battery Pack BP-820/BP-828, Canon AC Adapter CA-570 (included with camera), Canon Battery Charger CG-800/CG-800E, Canon HDMI cable HTC-100/HTS-100S, Canon Wireless Controller WL-D89, Canon Tele Converter TL-U58, Canon Wide Attachment WA-U58, Canon Soft Carrying Case SC-1000/SC-2000, Canon Wrist Strap WS-20, Canon Shoulder Strap SS-600/SS-650, Canon PROTECT filter 58mm, Canon ND4-L filter 58mm, Canon ND8-L filter 58mm, Canon GPS Receiver GP-E2, Canon Remote Controller RC-V100, Canon Battery Video Light VL-10Li/VL-10LiII, Canon Battery Pack BP-900 series (for VL-10Li/VL-10LiII), Canon Compact Power Adapter CA910/920/930 (charges BP-900 series battery packs), Canon Car Battery Adapter CB-910/920 (for charging the BP-900 series), Canon Interface Cable IFC-300PCU/S / IFC-400PCU
<b>Auto Gain Control limit</b>	Wide DR Mode selected: 9 - 38dB (1 dB increments) Wide DR Mode Off: 0 - 38 dB (1 dB increments)		
<b>SHUTTER SPEED</b>		<b>BATTERY</b>	
<b>Control modes</b>	Auto, P, Tv, Manual	<b>Battery Pack</b>	Canon Battery Pack BP-820 (supplied), BP-828 (optional)
<b>Shutter speed (PAL)</b>	1/6 - 1/2000 sec. 1/2 - 1/500 sec in Low Light mode)	<b>Power Consumption (recording)</b>	UHD/(150Mbps/160Mbps)/25.00P: XA55: Approx. 5W XA50: Approx. 4.8W
<b>Slow Shutter (SLS)</b>	50.00P: Auto slow shutter On: 1/25 to 1/500 sec. Auto slow shutter Off: 1/50 to 1/500 sec. 25.00P: Auto slow shutter On: 1/12.5* to 1/500 sec. (*Display is 1/12) Auto slow shutter Off: 1/25 to 1/500 sec.	<b>Continuous Recording Time (approx.)</b>	UHD/(150Mbps/160Mbps)/25.00p: XA55: 145 mins (BP-820) / 220 Mins (BP-828) XA50: 150 mins (BP-820) / 230 Mins (BP-828) FHD/(35Mbps/45Mbps)/50.00p: XA55: 135 mins (BP-820) / 210 Mins (BP-828) XA50: 140 mins (BP-820) / 215 Mins (BP-828)
<b>Clear Scan</b>	No	<b>SIZE AND WEIGHT</b>	
<b>WHITE BALANCE</b>		<b>Dimensions</b>	Approx. 109 x 91 x 214 mm (main body only) Approx. 140 x 216 x 265 mm (Including lens hood, BP-820, mic holder unit, and handle unit)
<b>Auto</b>	Yes	<b>Weight (camera only)</b>	XA55: Approx. 970g XA50: Approx. 960g
<b>Preiset</b>	Daylight (Approx. 5,600K), Tungsten (Approx. 3,200K)	<b>Weight (fully equipped)</b>	XA55: Approx. 1445g XA50: Approx. 1435g (Including lens hood, BP-820, mic holder unit, handle unit and one memory card)
<b>Manual setting</b>	Colour Temperature range: 2,000-15,000K Default value for Set 1 and Set 2: 5,600K	<b>Operating temperature range</b>	Approx. 0 to 40 °C, 85 % (relative humidity) Approx. -5 to 45 °C, 60 % (relative humidity)
<b>SHOOTING MODES</b>		<b>Footnotes</b>	(1) All specifications are subject to change without notice
<b>Program AE</b>	AUTO Mode Manual Mode: P, Tv, Av, M (manual exposure), SCN (Portrait, Sports, Snow, Beach, Sunset, Night, Low Light, Spotlight, Fireworks)		
<b>Infrared shooting mode</b>	Yes (green or white)		
<b>Built-in IR lamp</b>	Yes, in detachable Handle Unit. Wavelength: 850nm (near-Infrared)		
<b>Look settings</b>	Standard, Neutral, Wide DR, Monochrome (Adjustment: Sharpness, Contrast, Colour Depth)		
<b>WI-FI &amp; GPS SPECIFICATIONS</b>			
<b>Wi-Fi</b>	No		
<b>GPS Information (Optional Accessory)</b>	Location (Latitude/Longitude/Altitude), Coordinated Universal Time (UTC), Satellite reception. (requires the optional GPS Receiver GP-E2)		
<b>MISCELLANEOUS</b>			
<b>Tally lamp</b>	Yes, in detachable Handle Unit		
<b>Colour Bars (PAL)</b>	Yes, SMPTE or EBU, with 1KHz Tone		
<b>Accessory shoe</b>	Yes (cold shoe)		
<b>Assignable buttons</b>	5 assignable buttons: Assignable to (AF/MF) / Face Only AF / Magnification / Focus Guide / BLC Always On / Powered IS / Auto Acquire WB / WB Priority / IR Light / Pre REC / Review Recording / PHOTO / Monitor Channel / Menu / Off		
<b>Custom dial</b>	Av / Tv / M / AGC Limit / Exposure Compensation / Off		

Live for the story\_

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
Canon Europa NV 2019

**A 1.0-TYPE CMOS SENSOR COMPACT 4K  
CAMCORDER WITH DUAL PIXEL CMOS AF  
AND 15X ZOOM LENS**

**XA55 / XA50**

The highly compact and lightweight XA55 / XA50 offers high quality 4K UHD image quality with beneficial features such as Dual Pixel CMOS AF, Canon 15x optical zoom lens and advanced Full HD image quality driven by utilising outstanding Over Sampling HD Processing.



Sales Start Date: June 2019

**PRODUCT DETAILS:**

Product Name	Mercury Code	EAN Code
XA55	3668C003AA	4549292139709
XA50	3669C003AA	4549292139723

**CONSUMABLES:**

Product Name	Mercury Code	EAN Code
Battery BP-820	8597B002AA	4960999984490
Battery BP-828	8598B002AA	4960999984520
Battery Charger CG-800	2590B003AA	4960999612188
Battery Charger CG-800E(B)	2590B006AA	4960999610573
Remote Controller RC-V100	9660B001AB	4549292014013
Video Light VL-10LiII	1729B001AA	4960999408316
Shoulder Strap SS-600	3122A001BA	4960999605913
Shoulder Strap SS-650	3123A001BA	4960999605951
Wrist Strap WS-20	3118A001BA	4960999600314
Soft carrying case SC-2000	9389A001AA	4960999209852
HDMI cable HTC-100	2384B001AA	4960999530383
GPS receiver GP-E2	6363B001AA	4960999848358
Tele-converter TL-U58	2493C001AA	4549292105391
Wide attachment WA-U58	2494C001AA	4549292105407



Live for the story\_

## A 1.0-TYPE CMOS SENSOR COMPACT 4K CAMCORDER WITH DUAL PIXEL CMOS AF AND 15X ZOOM LENS

# XA55 / XA50

The highly compact and lightweight XA55 / XA50 offers high quality 4K UHD image quality with beneficial features such as Dual Pixel CMOS AF, Canon 15x optical zoom lens and advanced Full HD image quality driven by utilising outstanding Over Sampling HD Processing.



### MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)
XA55 / XA50	3668C003AA 3669C003AA	EA	Each	1	360	301	269	3.55
		CT	Carton	1	615	373	290	4.42
		EP	Euro Pallet	9	120	80	102	49.8

### What's in the box?

- XA55 / XA50 EU BODY
- Lens cap
- Lens hood with lens barrier
- Microphone Holder Unit
- Screws for Microphone Holder Unit
- Handle Unit
- WL-D89 Wireless Controller
- Lithium Battery (For WL) CR2025
- CA-570 Compact Power Adapter
- Ferrite core
- AC Cable EU
- BP-820 Battery Pack

# Canon

Live for the story\_