PIXMA G6050


MULTIFUNCTIO-NALITY MEETS HIGH YIELDS WITH SMART CONNECTIVITY

Print, scan, copy and connect to the cloud via the Canon PRINT app. Refill ink tanks with enhanced mess-free bottles, boost uptime with a 350-sheet plain paper capacity and print up to 18,000 pages from 3 black bottles or 7,700 pages from a colour set¹, keeping the quality with a low cost-per-page.









- · Superb printing yields
- Smart connectivity
- Clear and sharp
- Full integration



Auto 2-sided Print











PRODUCT RANGE



PIXMA G6050



PIXMA G5050



PIXMA GM2050

PIXMA G6050 PIXMA G5050 PIXMA GM2050



TECHNICAL SPECIFICATIONS

PIXMA G6050

GENERAL SPECIFICATIONS

Functions

PRINTER SPECIFIC ATIONS Print Resolution

Print Technology

Mono Print Speed Colour Print Speed Photo Print Speed

Borderless Printing Two Sided Printing

CARTRIDGES AND VIELDS Standard Ink Cartridges

Cartridge Yield (Plain paper)

Cartridge Yield (Photo print)

PAPER SUPPORT Paper Types

Maximum Paper Input

Paper Sizes

Paper Weight

Wi-Fi, Ethernet, Print, Copy, Scan

Up to 4800 ^[1] x 1200 dpi

2 FINE Cartridges (Black and Colour) Refillable ink tank printer

Approx. 13.0 ipm Approx. 6.8 ipm [2]

Borderless 10x15cm : Approx. 37 seconds [3] Yes A4, LTR, 4"x6", 5"x7", 7"x10", 8"x10",

Square(5"x5",4"x4",89x89mm1

Auto Duplex Print (A4, A5, B5, Letter - Plain Paper)

GI=50 < PGRK> GI-50 <C> GI-50 < M> GI-50 <Y>

A4 colour documents printing [4]

Black: 6,000 pages Colour: 7,700 pages * Estimated supplemental yield 10x15cm colour photo printing [5] Colour: 2,200 photos

* Estimated supplemental yield

Plain Paper High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201) Photo Paper Pro Platinum (PT-101) Photo Paper Pro Luster (LU-101) Photo Paper Plus Semi-gloss (SG-201) Glossy Photo Paper "Everyday Use" (GP-501) Matte Photo Paper (MP-101)

Envelope

Rear Tray: Max. 20 sheets (photo paper) or

Max. 100 sheets (plain paper) Cassette: Max. 250 sheets (plain paper)

Rear Tray: A4, A5, B5, LTR, LGL, 4"x6", 5"x7", 7"x10",

Envelopes(DL, COM10), Square (5" x 5", 4"x4",89x89mm), Card Size(91 x 55mm)

[Custom size] width 55mm - 215.9 mm, length 89mm - 676mm

Cassette: A4, A5, B5, LTR [Custom size] width 148.0 mm - 215.9 mm, length

Rear Tray: Plain paper: 64 - 105 g/m² Canon photo paper: up to 300 g/m² (Photo Paper Pro Platinum PT-101)

Cassette: Plain paper: 64 - 105 g/m²

SCANNER SPECIFICATIONS Scanner Type

Scanner Resolution (Optical) Line Scanning Speed

Scanning Depth (Input / Output) Maximum Document Size

COPIER SPECIFICATIONS Copy Speed

Multiple Copy **Copy Functions**

Copy Zoom

Display Type & Size Display Languages

Interface Type - PC / Mac

Interface Type - Other

CIS flatbed photo and document scanner

1200 x 2400 dpi ^[6]

Colour: 3.5 ms/line/300dpi) Greyscale: 1.5 ms/line(300dpi) [7] Colour: RGB each 16bit/8bit Grevscale: 16 bit / 8 bit

A4/ITR

sFCOT: Approx. 20 sec ^[8] sESAT: Approx. 5.1 ipm ^[8]

99 copies (max.)

Document Copying, Photo Copying, Borderless copy, 2-sided copy, 2-on-1 and 4-on-1 copy, Frame erase copy, Disc Label Copy, ID copy

25 - 400% (in 1% increments)

Fit to page A5 to A4, B5 to A4, A4 to A5 and A4 to B5

32 Languages Selectable: Japanese/English(mm & inch)/German/French/Italian/Spanish/Dutch/ Portuguese/Norwegian/Swedish/Danish/Finnish/ Russian/Czech/Hungarian/Polish/Slovene/Turkish/ Greek/Simplified Chinese/Traditional

Chinese/Korean/Indonesian/Slovakian/Estonian/

Latvian/Lithuanian/Ukrainian/Romanian/ Bulgarian/Croatian/Vietnamese

Hi-Speed USB (B Port) Ethernet: 10/100Mbps (auto switchable)

Wi-Fi: IEEE802.11 b/g/n Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP,

Administration password Wireless LAN Frequency Band: 2.4GHz Canon PRINT Inkjet/SELPHY app

Easy-PhotoPrint Editor Message In Print app

PIXMA Cloud Link

Canon Print Service Plugin (Android)

Google Cloud Print Apple AirPrint Wireless Direct Access Point Mode LAN/WLAN PictBridge Mopria (Android)

TECHNICAL SPECIFICATIONS

PIXMA G6050

SOFTWARE

Supported Operating Systems

Supported Mobile Systems

Minimum System Requirements

Software Included

Windows 10, Windows 8.1, Windows 7 SP1

Operation can only be guaranteed on a PC with pre-installed Windows 7 or later

Printer driver and IJ Network Device Setup Utility are

available with following OS. Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016

OS X 10.10.5~OS X 10.11, macOS 10.12~macOS

iOS, Android, Windows 10 Mobile

Windows: 2.0GB or more

Mac: 1.0GB or more

Note: for bundled software installation. The necessary amount of hard disk space required.

Display: 1024 x 768 XGA

Printer Driver

LI Printer Assistant Tool Easy-PhotoPrint Editor (download)

PHYSICAL FEATURES Weiaht

Dimensions (W x D x H) Acoustic Noise Levels Operating Temperature

Operating Humidity Power Source

Power Consumption

Typical Electricity Consumption (TEC) approx. 8.1kg approx. 403 x 369 x 195 mm approx. 50.5dB(A) [9]

10-90%RH (no dew condensation)

AC. 100-240V. 50/60Hz

Off: Approx. 0.3W

Standby (connected to PC via USB): Approx. 0.8W (scanning lamp off)

Standby (all ports connected): Approx. 1.7W

(scanning lamp is off)

Time to enter Standby mode: 11min 10sec Copying (USB connection to PC): Approx. 15W [10]

Footnotes

- [1] Ink droplets can be placed with a minimum pitch of 1/4800 inch
- [2] A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.
- Photo print speed is based on default driver setting using ISO/JIS-SCID N2 standard on Canon Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
- 14) Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart and continuous printing simulation with the replacement ink bottles after initial setup.
- [5] Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement ink bottles after initial setup.
- (4) Optical resolution is a measure of maximum hardware sampling resolution based on ISO 14473 standard. When scanning in high resolution, the maximum scan size is restricted
- [7] The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.
- 181 Colour document copy speed is measured based on average of sFCOT and sESAT in Performance Test of ISO/IEC 29183 standard. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- [9] Plain Paper(A4, B/W). Acoustic Noise is measured based on ISO7779 standard.
- [19] Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- [11] Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.

Standard disclaimers

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.

Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2019



MULTIFUNCTIONALITY MEETS HIGH YIELDS WITH SMART CONNECTIVITY

PIXMA G6050

Print, scan, copy and connect to the cloud via the Canon PRINT app. Refill ink tanks with enhanced messfree bottles, boost uptime with a 350-sheet plain paper capacity and print up to 18,000 pages from 3 black bottles or 7,700 pages from a colour set¹, keeping the quality with a low cost-per-page.

Sales Start Date: Jun 2019



PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
PIXMA G6050	3113C006AA	4549292141085

CONSUMABLES:

Product Name	Mercury Code	EAN Code
GI-50 <pgbk></pgbk>	3386C001AA	4549292134155
GI-50 <c></c>	3403C001AA	4549292134179
GI-50 <m></m>	3404C001AA	4549292134193
GI-50 <y></y>	3405C001AA	4549292134216



MULTIFUNCTIONALITY MEETS HIGH YIELDS WITH SMART CONNECTIVITY

PIXMA G6050

Print, scan, copy and connect to the cloud via the Canon PRINT app. Refill ink tanks with enhanced messfree bottles, boost uptime with a 350-sheet plain paper capacity and print up to 18,000 pages from 3 black bottles or 7,700 pages from a colour set¹, keeping the quality with a low cost-per-page.



MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)	Net Weight (kg)
PIXMA G6050	3113C006AA	Individual	1	495.0	538.0	288.5	11.6	9.4
	Pallet (Upper)	Pallet (Upper)	16	1003.0	1089.0	1158.5	171.0	TBC
		Pallet (Bottom)	16	1003.0	1089.0	1158.5	171.0	TBC

What's in the box?

- Multifunctional refillable ink tank printer Canon PIXMA G6050
- 6 high yield ink bottles (3x Black and 1x C/M/Y)
- · Power cord

- Setup CD-ROM
- Manuals and other documents

