

# EOS M200

## EINFACH UNGLAUBLICH, UNGLAUBLICH EINFACH

Überwinde die Grenzen deines Smartphones. Mit dieser intuitiv bedienbaren EOS Kamera, mit der du ganz einfach professionell wirkende Aufnahmen machst kannst du deine Erinnerungen auf eine neue Art erleben. Wechsle die Objektivs und halte die Stimmung jeder Situation im Bild fest - auch bei wenig Licht.



- **24.1 Megapixel APS-C Sensor**  
Begeisterung pur: unglaubliche Details und beeindruckende Farben
- **4K Video und HD-Videos mit bis zu 120B/s**  
Detailreiche Aufnahmen, auch in Zeitlupe
- **Dual Pixel CMOS AF**  
Schnell für Fotos, gleichmäßig bei Video - auch bei wenig Licht bis -4EV
- **Kompakt und leicht**  
Die besonderen Momente des Lebens ganz einfach mit der Kamera festhalten – so wie sie es verdienen
- **Kreativ-Assistent**  
Ganz einfach professionell aussehende Fotos aufnehmen
- **Bluetooth und WLAN**  
Zum Fernsteuern der Kamera und Teilen der Aufnahmen
- **180° klappbares Touchscreen-LCD**  
Für kreative Bilder und Selfies
- **Zeitraffer-Movies**  
Bewegungen in anderen Zeitdimensionen aufzeichnen

**24.1** MEGA  
PIXELS  
CMOS

**EOS Movie**  
4K+FULL HD

**Dual Pixel** AF  
CMOS

Wi-Fi  
Bluetooth®

Tilt-up LCD  
180°

4K  
4K Time-Lapse  
Movie

**PRODUKT RANGE**

EOS M6 Mark II  
EOS M50  
EOS M200



EOS M6 Mark II



EOS M50



EOS M200

**Canon**

Live for the story\_

<b>IMAGE SENSOR</b>		<b>SHUTTER</b>	
<b>Type</b>	22.3 x 14.9mm CMOS	<b>Type</b>	Vertical-travel mechanical focal-plane shutter, electronically controlled at all speeds
<b>Effective Pixels</b>	Approx. 24.1 megapixels	<b>Speed</b>	30 - 1/4000 sec (1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)
<b>Total Pixels</b>	Approx 25.8 megapixels		
<b>Aspect Ratio</b>	3:2	<b>WHITE BALANCE</b>	
<b>Low-Pass Filter</b>	Built-in/Fixed	<b>Type</b>	Auto white balance with the imaging sensor
<b>Sensor Cleaning</b>	EOS integrated cleaning system	<b>Settings</b>	Auto (Ambience Priority), Auto (White Priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature (100 Kelvin increments)
<b>Colour Filter Type</b>	Primary Colour	<b>Custom White Balance</b>	Yes, 1 setting can be registered
		<b>WHITE BALANCE Compensation</b>	1. Blue/Amber +/-9 levels 2. Magenta/ Green +/-9 levels
<b>IMAGE PROCESSOR</b>			
<b>Type</b>	DIGIC 8		
<b>LENS</b>		<b>VIEWFINDER</b>	
<b>Lens Mount</b>	EF-M (EF and EF-S lenses compatible via Mount adapter EF-EOS M)	<b>LCD MONITOR</b>	
<b>Focal Length</b>	Equivalent to 1.6x the focal length of the lens	<b>Type</b>	7.5 cm (3.0") Touchscreen LCD (TFT). 3:2 aspect ratio. Approx. 1,040,000 dots. Electrostatic capacitive type. Tilting approx 180° upward
<b>Image Stabilisation</b>	Optical Image Stabilizer on compatible lens	<b>Coverage</b>	Approx 100%
	Movie: In-camera Digital IS available. Further stabilisation enhancements from lenses compatible with Dynamic IS	<b>Viewing Angle (horizontally/vertically)</b>	Approx 170° horizontally and vertically
		<b>Brightness Adjustment</b>	Adjustable to one of seven levels
<b>FOCUSING</b>		<b>Display Options</b>	Customisable and toggle via INFO. Button (1) Liveview image with exposure info (2) Liveview image with basic info (3) Liveview image with full info
<b>Type</b>	Dual Pixel CMOS AF System. Phase detection pixels built onto imaging sensor <sup>[20]</sup>		
	Contrast detection method is used during 4K Movie and 4K Timelapse Movie	<b>FLASH</b>	
<b>AF System/ Points</b>	Maximum 143 points depending on lens.  Max 25 frames in Zone AF <sup>[15]</sup>	<b>Built-in Flash GN (ISO 100, meters)</b>	5
	Freely position 1 AF point/ 1 AF Zone via manual selection (area available lens dependent)	<b>Built-in Flash Coverage</b>	Maximum coverage at approx. 15mm (35mm equivalent: approx. 24mm)
<b>AF working range</b>	EV -4 - 18 (room temperature, f/1.4, ISO 100, One-Shot AF), Movie: EV -2 - 18 (room temperature, f/1.4, ISO 100, One-Shot AF, 29.97fps/25fps)	<b>Built-in Flash recycle time</b>	Approx. 4 seconds <sup>[27]</sup>
	One-Shot AF and Servo AF	<b>Modes</b>	Auto (E-TL II)
<b>AF Modes</b>	Face + Tracking (Eye Detection AF available)	<b>Red-Eye Reduction</b>	Provided
<b>AF Point Selection</b>	Zone AF  1-point AF	<b>X-sync</b>	1/200sec
	Spot AF	<b>Flash Exposure Compensation</b>	+/- 2 EV in 1/3 increments
<b>Selected AF point display</b>	Indicated on LCD monitor	<b>Flash Exposure Lock</b>	Yes
<b>AF Lock</b>	Locked when shutter button is pressed half way or AE Lock Button	<b>Second Curtain Synchronisation</b>	Yes
<b>AF Assist Beam</b>	via LED assist beam	<b>Ho/Shoe/ PC terminal</b>	No/No
<b>Manual Focus</b>	With EF & EF-S lenses - Select via AF/MF switch on lens  With EF-M lenses - Select via menu	<b>External Flash Compatibility</b>	none
	MF Peaking available AF+MF available (Manual focus adjustment after One-Shot AF) Magnify image available during MF (5x or 10x)	<b>SHOOTING</b>	
<b>Focus Bracketing</b>		<b>Modes</b>	Scene Intelligent Auto, Hybrid Auto, Creative Assist, SCN(Self-Portrait, Portrait, Smooth Skin, Landscape, Sports, Close-up, Food, Night Portrait, Handheld Night Scene, HDR Backlight Control), Creative Filters (Grainy B/W, Soft Focus, Fish-eye Effect, Water painting effect, Toy camera effect, Miniature effect, HDR Art standard, vivid, bold, embossed), Program AE, Shutter priority AE, Aperture priority AE, Manual exposure, Movie (Movie auto exposure, Movie manual exposure, Time-lapse movie)
<b>AF Micro adjustment</b>		<b>Picture Styles</b>	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)
<b>EXPOSURE CONTROL</b>		<b>Colour Space</b>	sRGB and Adobe RGB
<b>Metering modes</b>	Real-time metering from the image sensor (1) Evaluative metering (384 zones) (2) Partial metering at center (approx. 5.8% of Live View Screen) (3) Center weighted average metering (4) Spot metering (approx. 2.9% of Live View Screen)		
<b>Metering Range</b>	Still image: EV -1 - 20 (at 23 °C, ISO 100) Movie: EV 0 - 20 (at 23 °C, ISO 100)		
<b>AE Lock</b>	Auto: In One-shot AF mode with evaluative metering exposure is locked when focus is achieved. Manual: By AE lock Button in creative zone modes.		
<b>Exposure Compensation</b>	+/-3 EV in 1/3 stop increments		
<b>AEB</b>			
<b>ISO Sensitivity<sup>(8)</sup></b>	100 - 25600 in 1/3 stop increments. Max in Auto can be set from 400 - 25600  4K Movie: 100 - 6400 in 1/3-stop increments. Full HD and HD Movie: ISO 100 - 12800 in 1/3-stop increments. ISO can be expanded to 25600		

<b>Image Processing</b>	<p>Highlight Tone Priority (standard and enhanced)                      Auto Lighting Optimizer (4 settings)                      Long exposure noise reduction                      High ISO speed noise reduction (4 settings + Multi Shot NR)                      Lens peripheral illumination correction                      Chromatic aberration correction                      Diffraction correction                      Digital Lens Optimizer</p> <p>Creative Assist:                      Presets                      Background Blur (5 settings)                      Brightness (19 levels)                      Contrast (9 levels)                      Saturation (9 levels)                      Color Tone 1 &amp; 2 (19 levels)                      Monochrome (Off/Black and white/Sepia/Blue/Purple/Green)</p>	<b>OTHER FEATURES</b>	
<b>Drive modes</b>		<b>Custom Functions</b>	6 custom functions
<b>Continuous Shooting</b>	<p>Single, Continuous, Self timer (2s, 10s, Continuous)                      One shot AF: Approx. 6.1 shots/sec <sup>[21]</sup></p> <p>With Servo AF: Approx. 4 shots/sec <sup>[22]</sup></p>	<b>Metadata Tag</b>	User copyright information (Author's Name, Copyright Details) Image rating (0-5 stars)
<b>LIVE VIEW MODE</b>		<b>Playback zoom</b>	15 steps plus smooth pinch-to-zoom
<b>Coverage</b>	Approx. 100% (horizontally and vertically)	<b>Display Formats</b>	(1) Single image with information (toggle options) (2) Single image (3) Index display (4/9/36/100 images) (4) Jump Display (1/10/custom number image, by shot date, by rating, by folder, by movies only, protected only)
<b>FILE TYPE</b>		<b>Slide Show</b>	Playback time: 1/2/3/5/10/30 seconds Repeat: On/Off Transition Effects: Off, Slide in 1-2, Fade 1-3 Brightness/ RGB
<b>Still Image Type</b>	<p>JPEG: Fine, Normal (Exif 2.31 compliant) / Design rule for Camera File system (2.0)                      RAW: RAW (CR3 14-bit),                      Digital Print Order Format [DPOF] Version 1.1 compliant</p>	<b>Histogram</b>	Yes
<b>RAW+JPEG simultaneous recording</b>	Yes, RAW + various JPEG compression possible	<b>Highlight Alert</b>	Erase: Single image, Selected images, Selected range, All images Protection: Selected images, Selected range, All images. Unprotect all images
<b>Image Size</b>	<p>RAW: (3:2) 6000 x 4000, (4:3) 5328 x 4000, (16:9) 6000 x 3368, (1:1) 4000 x 4000</p> <p>JPEG 3:2: (L) 6000 x 4000, (M) 3984 x 2656, (S1) 2976 x 1984, (S2) 2400 x 1600                      JPEG 4:3: (L) 5328 x 4000, (M) 3552 x 2664, (S1) 2656 x 1992, (S2) 2112 x 1600                      JPEG 16:9: (L) 6000 x 3368, (M) 3984 x 2240, (S1) 2976 x 1680 (S2) 2400 x 1344                      JPEG 1:1: (L) 4000 x 4000, (M) 2656 x 2656, (S1) 1984 x 1984, (S2) 1600 x 1600</p>	<b>Image Erase/Protection</b>	(1) Shooting menu (x8) (2) Playback menu (x4) (3) Connectivity menu (x2) (4) Setup menu (x5) (5) Display menu (6) My Menu
<b>Movie Type</b>	<p>In-camera RAW processing &amp; Image Resize available in playback</p> <p>MP4 [Video: MPEG-4 AVC/H.264, Audio: MPEG-4 AAC]</p>	<b>Menu Categories</b>	(6) My Menu 29 Languages
<b>Movie Size</b>	<p>4K - 3840 x 2160 (23.98, 25 fps)                      Full HD - 1920 x 1080 (59.94, 50, 29.97, 25fps)                      HD - 1280 x 720 (119.9, 100, 59.94, 50 fps)</p>	<b>Menu Languages</b>	English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Vietnamese, Indonesian, Hindi, Japanese
<b>Movie Length</b>	Max duration 29min 59sec, Max file size 4GB	<b>Firmware Update</b>	Firmware update possible by the user.
<b>Sound Files</b>		<b>INTERFACE</b>	
<b>Folders</b>	New folders can be created and selected	<b>Computer</b>	Hi-Speed USB (Micro USB)
<b>File Numbering</b>	(1) Continuous, Auto Reset (2) Manual Reset	<b>Other</b>	Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only, 1-11 ch), <sup>[17]</sup>
			Bluetooth <sup>®</sup> (Specification version 4.1, Bluetooth low energy technology) <sup>[23][25]</sup>
			HDMI (Micro - Type-D connector)
		<b>DIRECT PRINT</b>	
		<b>Canon Printers</b>	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
		<b>PictBridge</b>	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
		<b>STORAGE Type</b>	SD, SDHC, SDXC (UHS-I compatible)

## SUPPORTED OPERATING SYSTEM

### PC & Macintosh

For individual software see service and support sections

## SOFTWARE

### Browsing & Printing

### Image Processing

### Other

Digital Photo Professional, DPP Express for iPad  
Picture Style Editor, EOS Utility, Image Transfer Utility 2

Camera Connect app available on iOS and Android devices<sup>[25]</sup>

## POWER SOURCE

### Batteries

### Battery life

1 x Rechargeable Li-ion Battery LP-E12  
Approx. 315 shots (conforms to CIPA)<sup>[5]</sup>  
Eco Mode: Approx. 485 shots  
Movie Recording: Approx. 90 mins  
Playback time when playing back a slideshow of still images: Approx. 4 hrs 55mins

### Battery Indicator

### Power saving

4 levels  
Display off (15, 30 sec or 1, 3, 5, 10, 30 mins)  
Auto Power Down (30 sec or 1, 3, 5, 10 mins, Disable)  
ECO mode

### Power Supply & Battery

### Chargers

Battery charger LC-E12

Compact Power Adapter CA-PS700  
DC Coupler DR-E12

## PHYSICAL SPECIFICATIONS

### Body Materials

### Operating Environment

### Dimensions (WxHxD)

### Weight (body only)

Polycarbonate  
0 – 40 °C, 85% or less humidity  
108.2 x 67.1 x 35.1mm  
Approx 299g (black), 299g (white), CIPA testing standard including battery and memory card

## ACCESSORIES

### Cases / Straps

### Lenses

### Remote Controller/ Switch

### Other

EM-200DB  
EM-E2  
EF-M lenses  
All EF and EF-S lenses compatible via Mount adapter  
EF-EOS M  
Bluetooth Remote BR-E1  
Interface cable IFC-600PCU  
Mount Adapter EF-EOSM

All data is based on Canon standard testing methods except where indicated. Subject to change without notice.

<sup>[5]</sup>Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated

<sup>[8]</sup>Recommended Exposure Index

<sup>[15]</sup>Maximum number of AF frame is dependent on selected image aspect ratio

<sup>[17]</sup>Wi-Fi use may be restricted in certain countries or regions.

<sup>[20]</sup>Dual Pixel CMOS AF - AF is possible over an area of approx. 80% Vertical x 80% Horizontal of the frame

<sup>[21]</sup>Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Total number of frames captured and continuous shooting speed may vary depending on camera exposure settings, type of lens used, battery level, light level and memory card used.

<sup>[22]</sup>Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Under Servo AF, maximum continuous shooting speed and total number of frames captured depends on subject condition, camera settings and lens used

<sup>[23]</sup>Equipped with Bluetooth® low energy technology. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Canon Europe Ltd. is under license. Other trademarks and trade names are those of their respective owners.

<sup>[25]</sup>Bluetooth functionality with Camera Connect app requires smart device to be equipped with Bluetooth version 4.0 (or later). Also requires smart device to be using operating system iOS 8.4 (or later) or Android 5.0 (or later)

<sup>[27]</sup>When battery is fully charged

# EINFACH UNGLAUBLICH, UNGLAUBLICHEINFACH

# EOS M200

Überwinde die Grenzen deines Smartphones. Mit dieser intuitiv bedienbaren EOS Kamera, mit der du ganz einfach professionell wirkende Aufnahmen machst kannst du deine Erinnerungen auf eine neue Art erleben. Wechsle die Objektivs und halte die Stimmung jeder Situation im Bild fest - auch bei wenig Licht.

Verkaufsstart: Oktober 2019



## DETAILS ZUM PRODUKT:

Produktname	Mercury Code	EAN Code
Digitalkamera EOS M200 BK M15-45 EU26	3699C010AA	4549292142280
Digitalkamera EOS M200 WH M15-45 SEU26	3700C010AA	4549292142297
Digitalkamera EOS M200 BK M15-45+M55-200 EU26	3699C018AA	4549292142976

## OPTIONAL ERHÄLTliches ZUBEHÖR:

Zubehörbezeichnung	Mercury-Code	EAN Code
<b>Stromversorgung</b>		
Akkuladegerät LC-E12E	6782B004AA	8714574626291
Akku LP-E12	6760B002AA	4960999911625
Netzadapter CA-PS700	7875A003AA	4960999112237
Gleichstromkuppel DR-E12	6785B001AA	4960999913278
<b>Kabel</b>		
USB-Kabel IFC-600U	1015C001AA	4549292054378
<b>Sonstiges</b>		
EF-EOS M Adapter	6098B005AA	4960999841137
EF-EOS M Adapter (ohne Stativanschluss)	0135T435	N/A
<b>Fernsteuerung</b>		
Kabellose Fernbedienung BR-E1	2140C001AA	4549292087864
Camera Connect App	N/A	N/A
<b>Schulter- und Tragegurte</b>		
Umhängegurt Schwarz EM-E2 (BK)	1661C001AA	4549292078596
Umhängegurt Braun EM-E2 (BW)	9930B001AA	4549292021257
Umhängegurt EM-200DB	9929B001AA	4549292021271
Canon Face Jacket EH31-FJ (Light Brown)	2261C001AA	4549292097153
Canon Face Jacket EH31-FJ(DB)	2262C001AA	4549292097184
Canon Face Jacket EH31-FJ(Yellow)	2263C001AA	4549292097207
Canon Face Jacket EH31-FJ(Navy)	2265C001AA	4549292097245
Canon Face Jacket EH31-FJ(Red)	2266C001AA	4549292100587
Canon Face Jacket EH31-FJ (Border blue)	2268C001AA	4549292097283

The Canon logo in its signature red font.

Live for the story\_

# EINFACH UNGLAUBLICH, UNGLAUBLICHEINFACH

# EOS M200

Überwinde die Grenzen deines Smartphones. Mit dieser intuitiv bedienbaren EOS Kamera, mit der du ganz einfach professionell wirkende Aufnahmen machen kannst, erlebst du deine Erinnerungen auf eine neue Art. Wechsle die Objektivs und halte die Stimmung jeder Situation im Bild fest - auch bei wenig Licht.

Verkaufsstart: Oktober 2019



## ABMESSUNGEN / LOGISTIKINFORMATIONEN:

Produktname	Mercury Code	Packart	Paketbeschreibung	Menge	Länge (ca. cm)	Breite (ca. cm)	Höhe (ca. cm)	Bruttogewicht (ca. kg)
Digitalkamera EOS M200 BK M15-45	3699C010AA	EA	Einzel	1	16,8	16,8	13,8	0,926
		CT	Karton	6	43,5	35,8	20,55	6,28
		EP	Europalette	150	120	80	118	167
			Lagen pro Palette	5				
			Kartons pro Lage	5				
			Produkte pro Lage	30				
Digitalkamera EOS M200 WH M15-45 SL	3700C010AA	EA	Einzel	1	16,8	16,8	13,8	0,921
		CT	Karton	6	43,5	35,8	20,55	6,28
		EP	Europalette	150	120	80	118	167
			Lagen pro Palette	5				
			Kartons pro Lage	5				
			Produkte pro Lage	30				
Digitalkamera EOS M200 BK M15-45+M55-200	3699C018AA	EA	Einzel	1	22,4	16,8	13,8	1,212
		CT	Karton	6	43,5	35,8	25,2	8,03
		EP	Europalette	120	120	80	115,8	171
			Lagen pro Palette	4				
			Kartons pro Lage	5				
			Produkte pro Lage	30				

## Lieferumfang

### EOS M200 BK M15-45

- Digitalkamera EOS M200 Gehäuse Schwarz
- Kamera-Gehäusedeckel R-F-4
- Tragegurt EM-200DB
- Akku LP-E12
- Akkuladegerät LC-E12E
- Netzkabel
- Anleitungen
- EF-M 15-45mm f/3.5-6.3 IS STM
- Objektivdeckel E-49
- Objektivrückdeckel EB

### EOS M200 WH M15-45

- Digitalkamera EOS M200 Gehäuse Weiß
- Kamera-Gehäusedeckel R-F-4
- Tragegurt EM-200DB
- Akku LP-E12
- Akkuladegerät LC-E12E
- Netzkabel
- Anleitungen
- EF-M 15-45mm f/3.5-6.3 IS STM
- Objektivdeckel E-49
- Objektivrückdeckel EB

### EOS M200 BK M15-45+M55-200

- Digitalkamera EOS M200 Gehäuse Schwarz
- Kamera-Gehäusedeckel R-F-4
- Tragegurt EM-200DB
- Akku LP-E12
- Akkuladegerät LC-E12E
- Netzkabel
- Anleitungen
- EF-M 15-45mm f/3.5-6.3 IS STM
- Objektivdeckel E-49
- Objektivrückdeckel EB EF-M55-200mm f/4.5-6.3 IS STM
- Objektivdeckel E-52 II
- Objektivrückdeckel EB

Live for the story\_