

# EOS M200

# SIMPLY

# INCREDIBLE,

# INCREDIBLY

# SIMPLE

Don't follow the smartphone crowd. Get closer to your memories with an easy-to-use, connected EOS camera that lets you shoot professional-looking photos, swap lenses and capture the ambience of any occasion – even in low light.



- Upgrade your photography
- Seamlessly connected to your digital life
- Unlock your creativity
- Go-anywhere design
- Complete the story with 4K video

**24.1** MEGA  
PIXELS  
CMOS

**EOS Movie**  
4K+FULL HD

**Dual Pixel AF**  
CMOS

Wi-Fi  
Bluetooth®

Tilt-up LCD  
180°

4K  
4K Time-Lapse  
Movie

## PRODUCT RANGE



EOS M6 Mark II



EOS M50



EOS M200

EOS M6 Mark II  
EOS M50  
**EOS M200**

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS M200

## IMAGE SENSOR

Type	22.3 x 14.9mm CMOS
Effective Pixels	Approx. 24.1 megapixels
Total Pixels	Approx 25.8 megapixels
Aspect Ratio	3:2
Low-Pass Filter	Built-in/Fixed
Sensor Cleaning	EOS integrated cleaning system
Colour Filter Type	Primary Colour

## IMAGE PROCESSOR

Type	DIGIC 8
------	---------

## LENS

Lens Mount	EF-M (EF and EF-S lenses compatible via Mount adapter EF-EOS M)
Focal Length	Equivalent to 1.6x the focal length of the lens
Image Stabilisation	Optical Image Stabilizer on compatible lens
	Movie: In-camera Digital IS available. Further stabilisation enhancements from lenses compatible with Dynamic IS

## FOCUSING

Type	Dual Pixel CMOS AF System, Phase detection pixels built onto imaging sensor <sup>[20]</sup>
	Contrast detection method is used during 4K Movie and 4K Timelapse Movie
AF System/ Points	Maximum 143 points depending on lens.
	Max 25 frames in Zone AF <sup>[15]</sup>

## AF working range

	EV -4 - 18 (room temperature, f/1.4, ISO 100, One-Shot AF), Movie: EV -2 - 18 (room temperature, f/1.4, ISO 100, One-Shot AF, 29.97fps/25fps)
--	---

## AF Modes

AF Point Selection	One-Shot AF and Servo AF
--------------------	--------------------------

	Face + Tracking (Eye Detection AF available)
	Zone AF
	1-point AF

## Selected AF point display

AF Lock	Indicated on LCD monitor
	Locked when shutter button is pressed half way or AE Lock Button
	via LED assist beam

## AF Assist Beam

Manual Focus	With EF & EF-S lenses - Select via AF/MF switch on lens
--------------	---

	With EF-M lenses - Select via menu
--	------------------------------------

	MF Peaking available
	AF+MF available (Manual focus adjustment after One-Shot AF)
	Magnify image available during MF (5x or 10x)

## Focus Bracketing

AF Micro adjustment	
---------------------	--

## EXPOSURE CONTROL

Metering modes	Real-time metering from the image sensor
	(1) Evaluative metering (384 zones)
	(2) Partial metering at center (approx. 5.8% of Live View Screen)
	(3) Center weighted average metering
	(4) Spot metering (approx. 2.9% of Live View Screen)
Metering Range	Still image: EV -1 - 20 (at 23 °C, ISO 100)
	Movie: EV 0 - 20 (at 23 °C, ISO 100)
AE Lock	Auto: In One-shot AF mode with evaluative metering exposure is locked when focus is achieved.
	Manual: By AE lock Button in creative zone modes.
	+/-3 EV in 1/3 stop increments

## Exposure Compensation

AEB	
ISO Sensitivity <sup>(8)</sup>	100 - 25600 in 1/3 stop increments. Max in Auto can be set from 400 - 25600

	4K Movie: 100 - 6400 in 1/3-stop increments. Full HD and HD Movie: ISO 100 - 12800 in 1/3-stop increments. ISO can be expanded to 25600
--	---

## SHUTTER

Type	Vertical-travel mechanical focal-plane shutter, electronically controlled at all speeds
Speed	30 - 1/4000 sec (1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)

## WHITE BALANCE

Type	Auto white balance with the imaging sensor
Settings	Auto (Ambience Priority), Auto (White Priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature (100 Kelvin increments)
	White balance compensation:
	1. Blue/Amber +/-9 levels
	2. Magenta/ Green +/-9 levels
Custom White Balance	Yes, 1 setting can be registered

## VIEWFINDER

### LCD MONITOR

Type	7.5 cm (3.0") Touchscreen LCD (TFT). 3:2 aspect ratio. Approx. 1,040,000 dots. Electrostatic capacitive type. Tilting approx 180° upward
Coverage	Approx 100%
Viewing Angle (horizontally/vertically)	Approx 170° horizontally and vertically
Brightness Adjustment	Adjustable to one of seven levels
Display Options	Customisable and toggle via INFO. Button
	(1) Liveview image with exposure info
	(2) Liveview image with basic info
	(3) Liveview image with full info

## FLASH

Built-in Flash GN (ISO 100, meters)	5
Built-in Flash Coverage	Maximum coverage at approx. 15mm (35mm equivalent: approx. 24mm)
	Approx. 4 seconds <sup>[27]</sup>
Built-in Flash recycle time	Auto (E-TTL II)
Modes	Provided
Red-Eye Reduction	1/200 sec
X-sync	+/- 2 EV in 1/3 increments
Flash Exposure Compensation	Yes
Flash Exposure Lock	Yes
Second Curtain Synchronisation	No/No
HotShoe/ PC terminal	none
External Flash Compatibility	

## SHOOTING

Modes	Scene Intelligent Auto, Hybrid Auto, Creative Assist, SCN(Self-Portrait, Portrait, Smooth Skin, Landscape, Sports, Close-up, Food, Night Portrait, Handheld Night Scene, HDR Backlight Control), Creative Filters (Grainy B/W, Soft Focus, Fish-eye Effect, Water painting effect, Toy camera effect, Miniature effect, HDR Art standard, vivid, bold, embossed), Program AE, Shutter priority AE, Aperture priority AE, Manual exposure, Movie (Movie auto exposure, Movie manual exposure, Time-lapse movie)
Picture Styles	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)
Colour Space	sRGB and Adobe RGB



# TECHNICAL SPECIFICATIONS

# EOS M200

<b>Image Processing</b>	<p>Highlight Tone Priority (standard and enhanced)            Auto Lighting Optimizer (4 settings)            Long exposure noise reduction            High ISO speed noise reduction (4 settings + Multi Shot NR)            Lens peripheral illumination correction            Chromatic aberration correction            Diffraction correction            Digital Lens Optimizer</p> <p>Creative Assist:            Presets            Background Blur (5 settings)            Brightness (19 levels)            Contrast (9 levels)            Saturation (9 levels)            Color Tone 1 &amp; 2 (19 levels)            Monochrome (Off/Black and white/Sepia/Blue/Purple/Green)</p> <p>Single, Continuous, Self timer (2s, 10s, Continuous)            One shot AF: Approx. 6.1 shots/sec <sup>[21]</sup></p> <p>With Servo AF: Approx. 4 shots/sec <sup>[22]</sup></p>	<b>OTHER FEATURES</b>	6 custom functions
<b>Drive modes</b>		<b>Custom Functions</b>	User copyright information (Author's Name, Copyright Details) Image rating (0-5 stars)
<b>Continuous Shooting</b>		<b>Metadata Tag</b>	15 steps plus smooth pinch-to-zoom (1) Single image with information (toggle options) (2) Single image (3) Index display (4/9/36/100 images) (4) Jump Display (1/10/custom number image, by shot date, by rating, by folder, by movies only, protected only) Playback time: 1/2/3/5/10/30 seconds Repeat: On/Off Transition Effects: Off, Slide in 1-2, Fade 1-3 Brightness/ RGB Yes
<b>LIVE VIEW MODE</b>		<b>Playback zoom</b>	
<b>Coverage</b>	Approx. 100% (horizontally and vertically)	<b>Display Formats</b>	
<b>FILE TYPE</b>		<b>Slide Show</b>	
<b>Still Image Type</b>	JPEG: Fine, Normal (Exif 2.31 compliant) / Design rule for Camera File system (2.0) RAW: RAW (CR3 14-bit), Digital Print Order Format [DPOF] Version 1.1 compliant	<b>Histogram</b>	
<b>RAW+JPEG simultaneous recording</b>	Yes, RAW + various JPEG compression possible	<b>Highlight Alert</b>	
<b>Image Size</b>	RAW: {3:2} 6000 x 4000, {4:3} 5328 x 4000, {16:9} 6000 x 3368, {1:1} 4000 x 4000	<b>Image Erase/Protection</b>	Erase: Single image, Selected images, Selected range, All images Protection: Selected images, Selected range, All images, Unprotect all images
	JPEG 3:2: (L) 6000 x 4000, (M) 3984 x 2656, (S1) 2976 x 1984, (S2) 2400 x 1600 JPEG 4:3: (L) 5328 x 4000, (M) 3552 x 2664, (S1) 2656 x 1992, (S2) 2112 x 1600 JPEG 16:9: (L) 6000 x 3368, (M) 3984 x 2240, (S1) 2976 x 1680 (S2) 2400 x 1344 JPEG 1:1: (L) 4000 x 4000, (M) 2656 x 2656, (S1) 1984 x 1984, (S2) 1600 x 1600	<b>Menu Categories</b>	(1) Shooting menu (x8) (2) Playback menu (x4) (3) Connectivity menu (x2) (4) Setup menu (x5) (5) Display menu (6) My Menu
<b>Movie Type</b>	In-camera RAW processing & Image Resize available in playback MP4 [Video: MPEG-4 AVC/H.264, Audio: MPEG-4 AAC]	<b>Menu Languages</b>	29 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Vietnamese, Indonesian, Hindi, Japanese
<b>Movie Size</b>	4K - 3840 x 2160 (23.98, 25 fps) Full HD - 1920 x 1080 (59.94, 50, 29.97, 25fps) HD - 1280 x 720 (119.9, 100, 59.94, 50 fps) Max duration 29min 59sec, Max file size 4GB	<b>Firmware Update</b>	Firmware update possible by the user.
<b>Movie Length</b>		<b>INTERFACE</b>	
<b>Sound Files</b>		<b>Computer</b>	Hi-Speed USB (Micro USB)
<b>Folders</b>	New folders can be created and selected	<b>Other</b>	Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only, 1-11 ch), <sup>[17]</sup>
<b>File Numbering</b>	(1) Continuous, Auto Reset (2) Manual Reset	<b>Bluetooth®</b> (Specification version 4.1, Bluetooth low energy technology) <sup>[23] [25]</sup>	
		<b>Other</b>	HDMI (Micro - Type-D connector)
		<b>DIRECT PRINT</b>	
		<b>Canon Printers</b>	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
		<b>PictBridge</b>	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
		<b>STORAGE</b>	
		<b>Type</b>	SD, SDHC, SDXC (UHS-I compatible)

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS M200

## SUPPORTED OPERATING SYSTEM

### PC & Macintosh

For individual software see service and support sections

## SOFTWARE

### Browsing & Printing Image Processing Other

Digital Photo Professional, DPP Express for iPad  
Picture Style Editor, EOS Utility, Image Transfer Utility 2

Camera Connect app available on iOS and Android devices <sup>[25]</sup>

## POWER SOURCE

### Batteries

#### Battery life

1 x Rechargeable Li-ion Battery LP-E12  
Approx. 315 shots (conforms to CIPA) <sup>[5]</sup>  
Eco Mode: Approx. 485 shots  
Movie Recording: Approx. 90 mins  
Playback time when playing back a slideshow of still images: Approx. 4 hrs 55mins

#### Battery Indicator

4 levels

#### Power saving

Display off (15, 30 sec or 1, 3, 5, 10, 30 mins)  
Auto Power Down (30 sec or 1, 3, 5, 10 mins, Disable)  
ECO mode

#### Power Supply & Battery Chargers

Battery charger LC-E12

Compact Power Adapter CA-PS700  
DC Coupler DR-E12

## PHYSICAL SPECIFICATIONS

### Body Materials

Polycarbonate

### Operating Environment

0 – 40 °C, 85% or less humidity

### Dimensions (WxHxD)

108.2 x 67.1 x 35.1mm

### Weight (body only)

Approx 299g (black), 299g (white), CIPA testing standard including battery and memory card

## ACCESSORIES

### Cases / Straps

EM-200DB  
EM-E2

### Lenses

EF-M lenses  
All EF and EF-S lenses compatible via Mount adapter  
EF-EOS M

### Remote Controller/ Switch

Bluetooth Remote BR-E1

### Other

Interface cable IFC-600PCU  
Mount Adapter EF-EOSM

All data is based on Canon standard testing methods except where indicated.  
Subject to change without notice.

<sup>[5]</sup> Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated

<sup>[6]</sup> Recommended Exposure Index

<sup>[15]</sup> Maximum number of AF frame is dependent on selected image aspect ratio  
<sup>[17]</sup> Wi-Fi use may be restricted in certain countries or regions.

<sup>[20]</sup> Dual Pixel CMOS AF - AF is possible over an area of approx. 80% Vertical x 80% Horizontal of the frame

<sup>[21]</sup> Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Total number of frames captured and continuous shooting speed may vary depending on camera exposure settings, type of lens used, battery level, light level and memory card used.

<sup>[22]</sup> Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Under Servo AF, maximum continuous shooting speed and total number of frames captured depends on subject condition, camera settings and lens used

<sup>[23]</sup> Equipped with Bluetooth® low energy technology. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Canon Europe Ltd. is under license. Other trademarks and trade names are those of their respective owners.

<sup>[25]</sup> Bluetooth functionality with Camera Connect app requires smart device to be equipped with Bluetooth version 4.0 (or later). Also requires smart device to be using operating system iOS 8.4 (or later) or Android 5.0 (or later)

<sup>[27]</sup> When battery is fully charged



Live for the story\_

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
Canon Europa NV 2019

# SIMPLY INCREDIBLE, INCREDIBLY SIMPLE

# EOS M200

Don't follow the smartphone crowd. Get closer to your memories with an easy-to-use, connected EOS camera that lets you shoot professional-looking photos, swap lenses and capture the ambience of any occasion – even in low light.

Sales Start Date: October 2019



#### PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
D.CAM EOS M200 BK M15-45 EU26	3699C010AA	4549292142280
D.CAM EOS M200 WH M15-45 SEU26	3700C010AA	4549292142297
D.CAM EOS M200 BK M15-45+M55-200 EU26	3699C018AA	4549292142976

#### OPTIONAL ACCESSORIES:

Accessory Name	Mercury Code	EAN Code
<b>Power Supply</b>		
Battery Charger LC-E12E	6782B004AA	8714574626291
Battery Pack LP-E12	6760B002AA	4960999911625
AC Adapter CA-PS700	7875A003AA	4960999112237
DC Coupler DR-E12	6785B001AA	4960999913278
<b>Cables</b>		
Interface Cable IFC-600U	1015C001AA	4549292054378
<b>Miscellaneous</b>		
EF-EOS M Mount Adapter	6098B005AA	4960999841137
EF-EOS M Mount Adapter (without a tripod)	0135T435	N/A
<b>Remote control</b>		
Wireless Remote-Control BR-E1	2140C001AA	4549292087864
Camera connect app	N/A	N/A

Live for the story\_

# SIMPLY INCREDIBLE, INCREDIBLY SIMPLE

# EOS M200

Don't follow the smartphone crowd. Get closer to your memories with an easy-to-use, connected EOS camera that lets you shoot professional-looking photos, swap lenses and capture the ambience of any occasion – even in low light.



#### OPTIONAL ACCESSORIES:

Accessory Name	Mercury Code	EAN Code
<b>Cases, jackets &amp; straps</b>		
Neck Strap Black EM-E2 (BK)	1661C001AA	4549292078596
Neck Strap Brown EM-E2 (BW)	9930B001AA	4549292021257
Neck Strap EM-200DB	9929B001AA	4549292021271
Canon Face Jacket EH31-FJ (Light Brown)	2261C001AA	4549292097153
Canon Face Jacket EH31-FJ(DB)	2262C001AA	4549292097184
Canon Face Jacket EH31-FJ(Yellow)	2263C001AA	4549292097207
Canon Face Jacket EH31-FJ(Navy)	2265C001AA	4549292097245
Canon Face Jacket EH31-FJ(Red)	2266C001AA	4549292100587
Canon Face Jacket EH31-FJ (Border blue)	2268C001AA	4549292097283

Live for the story\_

# SIMPLY INCREDIBLE, INCREDIBLY SIMPLE

# EOS M200

Don't follow the smartphone crowd. Get closer to your memories with an easy-to-use, connected EOS camera that lets you shoot professional-looking photos, swap lenses and capture the ambience of any occasion – even in low light.



## MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
D.CAM EOS M200 BK M15-45	3699C010AA	EA	Each	1	16.8	16.8	13.8	0.926
		CT	Carton	6	43.5	35.8	20.55	6.31
		EP	Euro Pallet	150	120	80	118	168
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAM EOS M200 WH M15-45 SL	3700C010AA	EA	Each	1	16.8	16.8	13.8	0.921
		CT	Carton	6	43.5	35.8	20.55	6.28
		EP	Euro Pallet	150	120	80	118	167
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
D.CAM EOS M200 BK M15-45+M55-200	3699C018AA	EA	Each	1	22.4	16.8	13.8	1.212
		CT	Carton	6	43.5	35.8	25.2	8.03
		EP	Euro Pallet	120	120	80	115.8	171
			Layers per Pallet	4				
			Cartons per Layer	5				
			Products per layer	30				

## What's in the box?

### D.CAM EOS M200 BK M15-45

- Digital Camera EOS M200 body Black
- Camera Cover R-F-4
- Strap EM-200DB
- Battery Pack LP-E12
- Battery Charger LC-E12E
- Power Cable
- User Manual Kit
- EF-M15-45mm f/3.5-6.3 IS STM
- Lens Cap E-49
- Lens Dust Cap EB

Live for the story\_

# SIMPLY INCREDIBLE, INCREDIBLY SIMPLE

Don't follow the smartphone crowd. Get closer to your memories with an easy-to-use, connected EOS camera that lets you shoot professional-looking photos, swap lenses and capture the ambience of any occasion – even in low light.

# EOS M200



## What's in the box?

### D.CAM EOS M200 WH M15-45 SL

- Digital Camera EOS M200 body White
- Camera Cover R-F-4
- Strap EM-200DB
- Battery Pack LP-E12
- Battery Charger LC-E12E
- Power Cable
- User Manual Kit
- EF-M15-45mm f/3.5-6.3 IS STM Silver
- Lens Cap E-49
- Lens Dust Cap EB

### D.CAM EOS M200 BK M15-45+M55-200

- Digital Camera EOS M200 body Black
- Camera Cover R-F-4
- Strap EM-200DB
- Battery Pack LP-E12
- Battery Charger LC-E12E
- Power Cable
- User Manual Kit
- EF-M15-45mm f/3.5-6.3 IS STM
- Lens Cap E-49
- EF-M55-200mm f/4.5-6.3 IS STM
- Lens Cap E-52 II
- Lens Dust Cap EB

**Canon**

---

Live for the story\_