

EOS R

**CAPTURE THE
FUTURE**

A pioneering full-frame EOS R camera for professionals and advanced enthusiasts

Building on over 30 years of EOS innovation and design heritage, EOS R sets the standard for the camera of tomorrow with a pioneering lens mount, offering responsive, high-speed auto-focus in as little as 0.05 seconds*.



- Greater creativity thanks to pioneering technology
- Capture more detail in photographs and video
- Use your EF and EF-S lenses via an adapter plus innovative RF optics
- Refined, responsive handling and ergonomics
- Connect and share images and movies with ease
- Shoot professional 4K video for breath-taking films

**Measured using CIPA-compliant guidelines, and internal measurement method with the lens RF24-105mm f/4 L IS USM mounted with one-shot AF in use.*

Canon

Live for the story_

TECHNICAL SPECIFICATIONS

EOS R

CAPTURE THE FUTURE

IMAGE SENSOR

Type	36 x 24 mm CMOS
Effective Pixels	Approx. 30.3 megapixels
Total Pixels	Approx. 31.7 megapixels
Aspect Ratio	3:2
Low-Pass Filter	Built-in/Fixed
Sensor Cleaning	EOS integrated cleaning system
Colour Filter Type	Primary Colour

IMAGE PROCESSOR

Type	DIGIC 8
------	---------

LENS

Lens Mount	RF (EF and EF-S lenses can be attached using Mount Adapter EF-EOS R, Control Ring Mount Adapter EF-EOS R, Drop-In Filter Mount Adapter EF-EOS R. EF-M lenses not compatible)
Focal Length	Equivalent to 1.0x the focal length of the lens with RF and EF lenses 1.6x with EF-S

FOCUSING

Type	Phase-difference detection system with image sensor (Dual Pixel CMOS AF)
AF Zones	With Area 88% horizontal and 100% vertical
AF working range	EV -6 to 18 (23 °C, ISO 100)
AF Modes	One-Shot AF, Servo AF
AF Point Selection	Automatic selection: Face + tracking, 143 Available AF areas when automatically selected Manual selection: 1-point AF (AF frame size can be changed) 5655 AF positions available Manual selection: AF point Expansion 4 points (up, down, left, right) Manual selection: AF point Expansion surrounding Manual selection: Zone AF (all AF points divided into 9 focusing zones) Manual selection: Large Zone AF (Vertical) Manual selection: Large Zone AF (Horizontal)
AF Lock	Locked when shutter button is pressed halfway or AF ON is pressed in One Shot AF mode. Using customised button set to AF stop in AI servo
AF Assist Beam	Emitted by built in LED or optional dedicated Speedlite (flash)
Manual Focus	Selected on lens

EXPOSURE CONTROL

Metering modes	Real-time with image sensor, 384-zone metering. (1) Evaluative metering (linked to All AF points) (2) Partial metering (approx. 6.1% of viewfinder at centre) (3) Spot metering: Centre spot metering (approx. 2.7% viewfinder at centre) AF point-linked spot metering not provided (4) Centre weighted average metering
Metering Brightness Range	EV -3 to 20 (at 23 °C, ISO 100, with evaluative metering)
AE Lock	Auto: AE lock takes effect when focus is achieved Manual: By AE lock button in P, Av, Fv, Tv and M modes
Exposure Compensation	+/-3 EV in 1/3 or 1/2 stop increments (can be combined with AEB)
AEB	+/-3 EV in 1/3 or 1/2 stop increments
Anti-flicker shooting	Yes. Flicker detected at a frequency of 100 Hz or 120 Hz. Maximum continuous shooting speed may decrease
ISO Sensitivity (8)	Auto 100-40000 (in 1/3-stop or whole stop increments) ISO can be expanded to L:50, H1: 51200, H2: 102400
SHUTTER	
Type	Electronically controlled focal-plane shutter
Speed	30-1/8000 sec (1/2 or 1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)
Shutter Release	Soft touch electromagnetic release

WHITE BALANCE

Type	
Settings	

Custom White Balance

WB Bracketing

VIEWFINDER

Type	0.5-type OLED colour Electronic Viewfinder
Dot Count	3.69 Million dots (1280 x 960)
Coverage (Vertical/Horizontal)	Approx. 100%
Magnification	Approx. 0.76x (4)
Dot Count	3.69 Million dots (1280 x 960)
Eyepoint	Approx. 23mm (from eyepiece lens centre)
Dioptre Correction	-4 to +2 m ⁻¹ (diopetre)
Viewfinder Information	AF point information, Exposure level indicator, Number of remaining multiple exposures, Exposure compensation, HDR shooting, Highlight tone priority, Multiple-exposure shooting, ISO speed, Dual Pixel RAW shooting, Possible shots, Multi Shot Noise Reduction, Number of self-timer shooting, Digital Lens Optimizer, Maximum burst, AF method, Battery level, AF operation, Exposure simulation, Drive mode, AEB, Metering mode, FEB, Anti-flicker shooting, Still photo cropping, Shooting mode, Aspect ratio, Scene icons Auto Lighting Optimizer, AE lock Picture Style, Flash-ready, White balance, Flash off White balance correction, FE lock, Image Quality, High-speed sync, Bluetooth function, Shutter speed, Wi-Fi function, Multi-function lock warning, Histogram, Aperture Electronic level, Lens information

Depth of field preview

LCD MONITOR

Type	8.01 cm (3.15") Clear View LCD II, approx. 2.1 million dots. Vari-Angle
Coverage	Approx. 100%
Viewing Angle (horizontally/vertically)	Approx. 170° vertically and horizontally
Coating	Anti-reflection and Anti-smudge. Reinforced glass incorporated

Brightness Adjustment

Touch-screen operations

Display Options

FLASH

Modes	E-TTL II Auto Flash, Metered Manual
X-sync	1/200sec
Flash Exposure Compensation	+/- 3 EV in 1/3 increments with EX series Speedlite flashes
Flash Exposure Bracketing	Yes, with compatible External Flash
Flash Exposure Lock	Yes
Second Curtain Synchronisation	Yes, via Speedlite
Hot Shoe / PC terminal	Yes / No
External Flash Compatibility	E-TTL II with EX series Speedlite, wireless multi-flash support

External Flash Control

Auto white balance with the imaging sensor

AWB (Ambience priority/White priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature Setting

White balance compensation:

1. Blue/Amber +/-9

2. Magenta/ Green +/-9

Yes, 1 setting can be registered

+/-3 levels in single level increments

3, 2, 5 or 7 bracketed images per shutter release

Selectable Blue/Amber bias or Magenta/Green bias

0.5-type OLED colour Electronic Viewfinder

3.69 Million dots (1280 x 960)

Approx. 100%

Approx. 0.76x (4)

3.69 Million dots (1280 x 960)

Approx. 23mm (from eyepiece lens centre)

-4 to +2 m⁻¹ (diopetre)

AF point information, Exposure level indicator, Number of remaining multiple exposures, Exposure compensation, HDR shooting, Highlight tone priority, Multiple-exposure shooting, ISO speed, Dual Pixel RAW shooting, Possible shots, Multi Shot Noise Reduction, Number of self-timer shooting, Digital Lens Optimizer, Maximum burst, AF method, Battery level, AF operation, Exposure simulation, Drive mode, AEB, Metering mode, FEB, Anti-flicker shooting, Still photo cropping, Shooting mode, Aspect ratio, Scene icons Auto Lighting Optimizer, AE lock Picture Style, Flash-ready, White balance, Flash off White balance correction, FE lock, Image Quality, High-speed sync, Bluetooth function, Shutter speed, Wi-Fi function, Multi-function lock warning, Histogram, Aperture Electronic level, Lens information

Yes, via customised button

8.01 cm (3.15") Clear View LCD II, approx. 2.1 million dots. Vari-Angle

Approx. 100%

Approx. 170° vertically and horizontally

Approx. 100%

Approx. 170° vertically and horizontally

Anti-reflection and Anti-smudge. Reinforced glass incorporated

Manual: Adjustable to one of seven levels

Colour Tone Adjustment: 4 settings

Capacitive method with menu functions, Quick Control settings, playback operations, and magnified display. AF point selection in still and Movies, touch shutter is possible in still photo shooting

(1) Basic Camera settings

(2) Advance Camera settings

(3) Camera settings plus histogram and dual level display

(4) No info

(5) Quick Control Screen

E-TTL II Auto Flash, Metered Manual

1/200sec

+/- 3 EV in 1/3 increments with EX series Speedlite flashes

Yes, with compatible External Flash

Yes

Yes, via Speedlite

Yes / No

E-TTL II with EX series Speedlite, wireless multi-flash support

Via camera menu screen



TECHNICAL SPECIFICATIONS

EOS R

CAPTURE THE FUTURE

SHOOTING

Modes

Stills: Scene Intelligent Auto, Flexible priority AE, Program AE, Shutter priority AE, Aperture priority AE, Manual, Bulb and Custom (x3)
Movie: Scene Intelligent Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Bulb and Custom (x3)

Picture Styles

Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)

Colour Space

sRGB and Adobe RGB

Image Processing

Highlight Tone Priority
Auto Lighting Optimizer (4 settings)
Long exposure noise reduction
High ISO speed noise reduction (4 settings) (still and video)
Lens optical correction (3):
- Peripheral illumination correction, Chromatic aberration correction Distortion correction (during/after still photo shooting, during video only)
- Diffraction correction, Digital Lens Optimizer (during/after still photo shooting)
Resize to M, S1, S2 (6)
Cropping: JPEG images can be cropped (Aspect ratios 3:2, 4:3, 16:9, 1:1)
- 45 cropping sizes selectable, from 11% to 95% (diagonal)
- Switch between vertical and horizontal cropping orientation
- Image straightening
- Cropping frame can be moved using touch screen operation
RAW image processing (7)
Multiple exposure
HDR

Drive modes

Single, Continuous High, Continuous Low, Silent Single, Self timer (2s+remote, 10s+remote)

Continuous Shooting

Max. Approx. 8fps. speed maintained for 100 JPEG or 47 RAW images (1) (2) (10)
Max. 5fps with AF Tracking

Interval timer

Not supported

LIVE VIEW MODE

Type

Electronic viewfinder with image sensor

Coverage

Approx. 100% (horizontally and vertically)

Frame Rate

59.97 fps (smooth) / 29.97 fps (power saving)

Focusing

Manual Focus (Magnify the image 5x or 10x at any point on screen)
Autofocus: Dual Pixel CMOS AF (Face Detection and Tracking AF, 1point AF, Expand AF Area Zone AF, and Touch shutter

Metering

Real-time evaluative metering with image sensor (384-zone)
Partial metering (approx. 6.1% of the centre of the screen)
Spot metering (approx. 2.7% of the centre of the screen)
Centre-weighted average metering
Active metering timer can be changed

Display Options

3 levels available Basic shooting information, Advanced shooting information and Advanced shooting information with Histogram

FILE TYPE

Still Image Type

JPEG: 2 compression options
RAW: RAW, C-Raw and Dual Pixel RAW (14-bit, Canon original RAW 3rd edition)
Complies with Exif 2.31 and Design rule for Camera File system 2.0
Complies with Digital Print Order Format [DPOF] Version 1.1

RAW+JPEG simultaneous recording

Yes, any combination of RAW + JPEG possible, including Dual Pixel RAW + JPEG

Image Size

JPEG:

3:2 ratio (L, RAW, C-Raw) 6720x4480, (M1) 4464x2976, (S1) 3360x2240, (S2) 1696x1280
1.6x (crop) (L) 4176x2784, (S2) 2400x1600
4:3 ratio (L) 5952x4480, (M1) 3968x2976, (S1) 2976x2240, (S2) 2112x1600
16:9 ratio (L) 6720x3776, (M1) 4464x2512, (S1) 3360x1888, (S2) 2400x1344
1:1 ratio (L) 4480x4480, (M1) 2976x2976, (S1) 2240x2240, (S2) 1600x1600

EOS Movie

Movie Type

MOV Video: 4K (16:9) 3840 x 2160, Full HD, HD
MPEG4 AVC/H.264 variable (average) bit rate,
Audio: Linear PCM

Movie Size

4K (16:9) 3840 x 2160 (29.97, 25, 24, 23.98 fps) intra or inter frame (13)
Full HD (16:9) 1920 x 1080 (59.94, 50, 29.97, 25, 23.98 fps) intra or inter frame (13)
Full HD (16:9) 1920 x 1080 HDR (29.97, 25 fps) inter frame (13)
Full HD (16:9) 1920 x 1080 (29.97, 25) light inter frame HD (16:9) 1280 x 720 (119.9, 100 fps) intra frame

Colour Sampling (Internal recording)

Canon Log

Movie Length

4K - YCbCr4:2:2 (8-bit)
Full HD/HD - YCbCr4:2:0 (8-bit)
Yes, Log 1
4K and Full HD - Max duration 29min 59sec. (excluding High Frame Rate movies). No 4GB file limit with exFAT CF card.

High Frame Rate Movie

MOV Video: HD - 1280 x 720 at 100fps or 119.9fps
Recorded as 1/4-speed slow motion movie
Single scene maximum recording up to 7min 29sec.
8.3-megapixel JPEG still image frame grab from 4K movie possible

4K Frame Grab

Bitrate/Mbps

MOV:
4K (29.97p/25.00p/24.00p/23.98p): ALL-I Approx. 480 Mbps
4K (29.97p/25.00p/24.00p/23.98p): IPB Approx. 120 Mbps
Full HD (59.94p/50.00p)/ALL-I: Approx. 180 Mbps
Full HD (59.94p/50.00p)/IPB Approx. 60 Mbps
Full HD (29.97p/25.00p/24.00p/23.98p)/ALL-I: Approx. 90 Mbps
Full HD (29.97p/25.00p/24.00p/23.98p)/IPB: Approx. 30 Mbps
HD (119.9p/100.0p)/ALL-I: Approx. 160 Mbps

Microphone

MP4:
Full HD (29.97p/25.00p)/IPB (Light): Approx. 12 Mbps
Built-in stereo microphones (48 Khz, 16-bit x 2 channels)

HDMI Display

External Monitor only, External Monitor only without information display or Simultaneous on camera and external monitor

HDMI Output

4K (UHD) recording only, uncompressed YCbCr 4:2:2, 8-bit or 10-bit, sound output via HDMI is also possible

Focusing

Dual Pixel CMOS AF with Face Detection and Tracking AF, Movie Servo AF
Manual Focus

ISO

4K - Auto: 100-12800, H: 25600, H1: 32000, H1: 51200, H2: 102400,
Full HD/HD - Auto: 100-25600, H: 32000, H1: 51200, H2: 102400

OTHER FEATURES

Custom Functions

22 Custom Functions

Metadata Tag

User copyright information (can be set in camera)
Image rating (0-5 stars)
IPTC data (registered with EOS Utility)
Image transfer with caption (Caption registered with EOS Utility)

LCD Panel / Illumination

Yes / Yes



TECHNICAL SPECIFICATIONS

EOS R

CAPTURE THE FUTURE

Water/Dust resistance	Yes
Voice Memo	No
Intelligent Orientation Sensor	Yes
Playback zoom	1.5x - 10x in 15 steps
Display Formats	(1) Single image (2) Single image with information (2 levels) Basic - Shooting information (shutter speed, aperture, ISO and Image quality) Detailed - Shooting information (shutter speed, aperture, ISO, metering Image, quality and file size), Lens information, Brightness and RGB histogram, White balance, Picture Style, Color space and noise reduction, Lens optical correction, GPS information, IPTC information (3) 4 image index (4) 9 image index (5) 36 image index (6) 100 image index (7) Jump Display (1, 10 or 100 images, Date, Folder, Movies, Stills, Protected images, Rating) (8) Movie edit (9) RAW processing (10) Rating
Slide Show	Image selection: All images, by Date, by Folder, Movies, Stills, Protected images or Rating Playback time: 1/2/3/5/10 or 20 seconds Repeat: On/Off
Histogram	Brightness: Yes RGB: Yes
Highlight Alert	Yes
Image Erase	Single image, select range, Selected images, Folder, Card
Image Erase Protection	Erase protection of Single image, Folder or Card all found images (only during image search)
Self Timer	2 or 10 sec.
Menu Categories	(1) Shooting menu (2) AF Menu (3) Playback menu (4) Setup menu (5) Custom Functions menu (6) My Menu
Menu Languages	29 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Vietnamese, Hindi, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Indonesia and Japanese
Firmware Update	Update possible by the user (Camera, Lens, WFT, External Speedlite, BLE remote control, Lens adapter)
INTERFACE	
Computer	SuperSpeed USB 3.1 USB C connector
Wi-Fi	Wireless LAN (IEEE802.11b/g/n) (2.4 GHz only), with Bluetooth support [12] Features supported - EOS Utility, Smartphone, Upload to Web, Wireless printing
Other	HDMI mini out (Type C, HDMI-CEC compatible), External Microphone In/Line In (Stereo mini jack), Headphone socket (Stereo mini jack), E3-type terminal (remote control terminal)
DIRECT PRINT	
PictBridge	Yes (via wireless LAN only)
STORAGE	
Type	1x SD/SDHC/SDXC and UHS-II
SUPPORTED OPERATING SYSTEMS	
PC & Macintosh	Windows 7 (excl. Starter Edition) Windows 8.1 and Windows 10 (tablet mode not supported) OS X v10.11, 10.12, 10.13 and 10.14

SOFTWARE

Image Processing

Other

POWER SOURCE

Batteries

Battery life

Battery Indicator

Power saving

Power Supply & Battery Chargers

Digital Photo Professional 4.9 or later (RAW Image Processing)

EOS Utility 3.9 or later (incl. Remote Capture), Picture Style Editor, Map Utility, EOS Lens Registration Tool, EOS Web Service Registration Tool, Canon Camera connect app (iOS/Android)

Rechargeable Li-ion Battery LP-E6N (supplied)/LP-E6

Approx. 370 shots (at 23°C) (5)

Approx. 350 (at 0°C)

6 levels + percentage

Power turns off after 30 seconds, 1, 3, 5, 10 or 30 mins

Battery charger LC-E6E (supplied), AC Adapter AC-E6N and DC Coupler DR-E6, AC Adapter Kit ACK-E6N/ACK-E6, Car Battery Charger CBC-E6, USB power adapter PD-E1

PHYSICAL SPECIFICATIONS

Body Materials

Operating Environment

Dimensions (WxHxD)

Weight (body only)

Magnesium Alloy body and polycarbonate with glass fibre parts

0 – 40 °C, 85% or less humidity

135.8 x 98.3 x 84.4mm

Approx. 580 g (660 g with card and battery)

ACCESSORIES

Wireless File Transmitter

Lenses

Lens adapters

Flashes

Remote Controller/Switch

Other

Wireless File Transmitter WFT-E7B

All RF lenses (EF & EF-S via Lens adapters)

Mount Adapter EF-EOS R, Control Ring Mount Adapter EF-EOS R, Drop-In Filter Mount Adapter EF-EOS R

Canon Speedlite (EL-100, 90EX, 220EX, 270EX, 270EX II, 320EX, 380EX, 420EX, 430EX, 430EX II, 430EX III 470EX-AI, 550EX, 580EX, 580EX II, 600EX, 600EX-RT, 600EX-II-RT, Macro-Ring-Lite MR-14EX, Macro Ring Lite MR-14EX II, Macro Twin Lite MT-24EX, Macro Twin Lite MT-26EX Speedlite Transmitter ST-E2, Speedlite Transmitter ST-E3-RT)

Remote control with E3 type socket and Speedlite 600EX-II-RT, Wireless Remote Control BR-E1

Battery grip BG-E22, GP-E2 GPS receiver

All data is based on Canon standard testing methods except where indicated.

Subject to change without notice.

1 Large/Fine resolution

2 Based on Canon's testing conditions, JPEG, ISO 100, Standard Picture Style. Maximum fps and buffer capacity may be reduced depending on the camera's settings, light level, subject, memory card brand and capacity, image recording quality, ISO speed, drive mode, Picture Style, Custom functions etc.

4 with 50mm lens at infinity, -1m-1 dpt

5 Based on the CIPA Standard and using the battery supplied with the camera, except where indicated

6 Frame grab images from 4K movies and images shot in S2 quality cannot be resized

7 RAW image processing during image Playback only with RAW and Dual Pixel RAW only

8 Recommended Exposure Index

10 Figures quoted are when used with UHS-II SD memory card

11 The AF area available vary depending on the lens used

12 Wi-Fi use may be restricted in certain countries or regions



Live for the story_

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2020

EOS R

CAPTURE THE FUTURE

Sales Start Date: October 2018



PRODUCT DETAILS:

Product Name	Mercury Code	GTIN Code
D.CAM EOS R BODY	3075C003AA	4549292119305
D.CAMERA EOS R BODY + Mount Adapter EF-EOS R EU26	3075C023AA	4549292119978
D.CAM EOS R RF 24-105 L EU26	3075C013AA	4549292119343
D.CAMERA EOS R RF 24-105mm f/4 L IS USM + Mount Adapter EF-EOS R EU26	3075C058AA	8714574659633
D.CAM EOS R + RF 24-105mm F4-7.1 IS STM EU26	3075C033AA	4549292171365

OPTIONAL ACCESSORIES:

Product Name	Mercury Code	GTIN Code
Power Supply		
CAMERA BATTERY PACK LP-E6N	9486B002AB	4549292008302
CAMERA BATTERY CHARGER LC-E6E	3349B001AA	4960999627502
USB Power Adapter PD-E1	3250C003AA	4549292125412
Cables		
USB Cable IFC-600PCU	1015C001AA	4549292054378
Interface Cable IFC-100U	3224C001AA	4549292124200
Interface Cable IFC-400U	3225C001AA	4549292124224
Interface Cable IFC-40AB III	3226C001AA	4549292124248
Interface Cable IFC-150AB III	3227C001AA	4549292124262
Miscellaneous		
Battery Grip BG-E22	3086C003AA	4549292119930
Camera Cover R-F-5	3201C001AA	4549292123852
Lenses		
LENS RF24-105MM F/4 L IS USM EU26	2963C005AA	4549292115611
LENS RF28-70MM F/2 L USM EU26	2963C007AA	8714574660066
LENS RF28-70MM F/2 L USM PREMIUM KIT CH	2965C005AA	4549292115642
LENS RF50MM F/1.2 L USM EU26	2965C006AA	8714574660080
LENS DUST CAP RF	2962C001AA	4549292115604
Canon EF or EF-S lenses (excluding EF-M lenses) * * Mount Adapter EF-EOS R required	N/A	N/A

Live for the story_

EOS R

CAPTURE THE FUTURE



OPTIONAL ACCESSORIES:

Product Name	Mercury Code	GTIN Code
Mount Adapter		
MT ADAPTER EF-EOS R	2971C005AA	4549292115703
CONTROL RING MOUNT ADAPTER EF-EOS R	2972C005AA	4549292115710
DIF MT ADAPTER EF-EOS R WITH V-ND FILTER	3443C005AA	4549292141610
DIF MT ADAPTER EF-EOS R WITH C-PL FILTER	3442C005AA	4549292141603
Flash related accessories		
Wireless Remote-Control BR-E1	2140C001AA	4549292087864
Remote Switch RS-60 E3	2469A002AA	4960999581354
USB Power Adapter PD-E1	3250C003AA	4549292125412
Speedlite 270EX II EUR	5247B003AA	4960999783246
Speedlite 320EX EUR	5246B003AA	4960999786032
Speedlite 430EX II EUR	2805B003AA	4960999617947
Speedlite 430EX III-RT	0585C003AA	4549292038262
Speedlite 600EX EUR	5739B003AA	4960999810195
Speedlite 600EX II-RT EU16	1177C006AA	8714574643281
Speedlite 600EX-RT EUR	5296B003AA	4960999786100
Speedlite 90EX	6825B003AA	4960999915111
Speedlite Bracket SB-E2	1949B001AA	4960999417264
Speedlite Transmitter ST-E2	2478A004AA	4960999581538
Speedlite Transmitter ST-E3-RT	5743B003AB	4960999810232

Live for the story_

EOS R

CAPTURE THE FUTURE

MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
D,CAM EOS R BODY	3075C003AA	EA	Each	1	28	22.3	14.7	1.479
		CT	Carton	6	47.7	47.1	31.4	10.2
		EP	Euro Pallet	36	120	80	109.2	68.6
			Layers per Pallet	3				
			Cartons per Layer	2				
			Products per layer	12				
D,CAM EOS R + RF 24-105mm F4-7.1 IS STM EU26	3075C033AA	EA	Each	1	28	22.3	18.4	2.02
		CT	Carton	3	58.6	24.4	32.2	6.91
		EP	Euro Pallet	54	120	80	111.6	134
			Layers per Pallet	3				
			Cartons per Layer	6				
			Products per layer	18				

What's in the box?

EOS R Body Only

- EOS R Body (Black)
- Camera Cover R-F-5
- Strap ER-EOSR
- Battery Charger LC-E6E
- Battery Pack LP-E6N
- Battery Pack Cover
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- User Manual Kit

EOS R Body + RF 24-105mm F4-7.1 IS STM

- EOS R Body
- Camera Cover R-F-5
- Strap ER-EOSR
- Battery Charger LC-E6E
- Battery Pack LP-E6N
- Battery Pack Cover
- AC Cable (EU/SK)
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- RF 24-105mm F4-7.1 IS STM
- Lens Cap E-67II
- Lens Dust Cap RF
- User Manual Kit



Live for the story_

EOS R

CAPTURE THE FUTURE

What's in the box?

EOS R BODY + Mount Adapter EF-EOS R

- EOS R Body (Black)
- Camera Cover R-F-5
- Strap ER-EOSR
- Battery Charger LC-E6E
- Battery Pack LP-E6N
- Battery Pack Cover
- AC Cable
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- Mount Adapter EF-EOS R
- Lens Dust Cap RF
- Camera Cover R-F-3
- User Manual Kit

EOS R Body + RF 24-105mm F4 L IS USM

- EOS R Body (Black)
- Camera Cover R-F-5
- Strap ER-EOSR
- Battery Charger LC-E6E
- Battery Pack LP-E6N
- Battery Pack Cover
- AC Cable
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- RF 24-105mm f/4 L IS USM
- Lens Cap E-77 II
- Lens Dust Cap RF
- Lens Hood EW-83N
- Lens Case LP1319
- User Manual Kit

EOS R + RF 24-105mm f/4 L IS USM + Mount Adapter EF-EOS R

- EOS R Body (Black)
- Camera Cover R-F-5
- Strap ER-EOSR
- Battery Charger LC-E6E
- Battery Pack LP-E6N
- Battery Pack Cover
- AC Cable
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- RF 24-105mm f/4 L IS USM
- Lens Cap E-77 II
- Lens Dust Cap RF
- Lens Hood EW-83N
- Lens Case LP1319
- Mount Adapter EF-EOS R
- Lens Dust Cap RF
- Camera Cover R-F-3
- User Manual Kit



Live for the story_