

# EOS M50 Mark II

# PUT YOUR PASSION IN THE SPOTLIGHT

If you're a content creator, the EOS M50 Mark II lets you communicate with your on-line audience on a whole new level. Perfect for vloggers, bloggers and influencers who want to step up from their smartphone and want to keep things simple and easy to use.



- Videos and photos your audience will love
- Smartphone simplicity and connectivity
- Smart tech that empowers you to be creative
- Shoot the way you want
- Captivating content that's easy to shoot

**24.1** MEGA  
PIXELS  
CMOS

FULL HD  
**60p**  
Recording

**4K**

Up to  
**10.0**  
Frames  
Per Sec

**Dual Pixel**  
CMOS **AF**

Eye Detection  
AF

## PRODUCT RANGE



EOS M6 Mark II



EOS M50 Mark II



EOS M200

EOS RP  
EOS M5  
EOS M6 Mark II  
**EOS M50 Mark II**  
EOS M200

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS M50 Mark II

## IMAGE SENSOR

Type	22.3 x 14.9mm CMOS
Effective Pixels	Approx. 24.1 megapixels
Total Pixels	Approx 25.8 megapixels
Aspect Ratio	3:2
Low-Pass Filter	Built-in/Fixed
Sensor Cleaning	EOS integrated cleaning system
Colour Filter Type	Primary Colour

## IMAGE PROCESSOR

Type	DIGIC 8
------	---------

## LENS

Lens Mount	EF-M (EF and EF-S lenses compatible via Mount adapter EF-EOS M)
Focal Length	Equivalent to 1.6x the focal length of the lens
Image Stabilisation	Optical Image Stabilizer on compatible lens Movie: In-camera Digital IS available. Further stabilisation enhancements from lenses compatible with Dynamic IS

## FOCUSING

Type	Dual Pixel CMOS AF System. Phase detection pixels built onto imaging sensor <sup>[1]</sup> Contrast detection method is used during 4K Movie Servo AF
------	--

## AF System/Points

Maximum 3975 positions  
Maximum 143/99 points available for automatic selection in Face+Tracking mode. May vary depending on settings.  
Max 25 frames in Zone AF <sup>[2]</sup>

AF working range	EV -4 - 18 (at 23 °C, ISO 100, with EF-M 32mm f/1.4 STM)
------------------	--

## AF Modes

AF Point Selection	One-Shot AF and Servo AF Face + Tracking: Face and subject tracking via automatic recognition/ manual selection via touchscreen. Automatic selection over AF points when no face recognised within frame. Eye AF available Zone AF: Manual zone selection, plus automatic selection over AF points within selected zone 1-point AF / Spot AF: Manual selection via touchscreen/ buttons
--------------------	---

## Selected AF point display

Indicated on LCD monitor/ EVF

## AF Lock

Locked when shutter button is pressed half way or customisable AE Lock Button

## AF Assist Beam

via LED assist beam

## Manual Focus

With EF & EF-S lenses - Select via AF/MF switch on lens  
With EF-M lenses - Select via dedicated MF button/ other customisable buttons (toggle AF/MF).  
MF Peaking available  
AF+MF available (Manual focus adjustment after One-Shot AF)  
Magnify image available during MF (5x or 10x)

## EXPOSURE CONTROL

### Metering modes

Real-time metering from the image sensor  
(1) Evaluative metering (384 zones)  
(2) Partial metering at center (approx. 5.8% of Live View Screen)  
(3) Center weighted average metering  
(4) Spot metering (approx. 2.9% of Live View Screen)  
Partial and spot metering not available in movie

### Metering Range

Still image: EV -2 - 20 (at 23 °C, ISO 100)  
Movie: EV 0 - 20 (at 23 °C, ISO 100)

## AE Lock

Auto: In One-shot AF mode with evaluative metering exposure is locked when focus is achieved.  
Manual: By AE lock Button in creative zone modes.

## Exposure Compensation

+/-3 EV in 1/3 stop increments

## AEB

3 shots, +/- 2 EV, 1/3-stop increments (can be used together with Exposure Compensation)

## ISO Sensitivity <sup>[3]</sup>

ISO AUTO (minimum 100, maximum can be set between 400 - 25600 except in Scene Intelligent Auto and Creative Filter mode max 6400, and Flash On 1600), ISO 100 - 25600 in 1/3 stop increments. ISO can be expanded to 51200

4K Movie: ISO AUTO (100 - 6400), 100 - 6400 in 1/3-stop increments. Full HD and HD Movie: ISO AUTO (100 - 12800), ISO 100 - 12800 in 1/3-stop increments. ISO can be expanded to 25600

## SHUTTER

Type	Electronically controlled focal-plane shutter
Speed	30 - 1/4000 sec (1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)

## WHITE BALANCE

Type	Auto white balance with the imaging sensor
Settings	Auto (Ambience Priority), Auto (White Priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature (100 Kelvin increments) White balance compensation: 1. Blue/Amber +/-9 levels 2. Magenta/ Green +/-9 levels Yes, 1 setting can be registered

## Custom White Balance

## VIEWFINDER

Type	0.39-type OLED Electronic Viewfinder Approx. 2,360,000 dots
Coverage (Vertical/Horizontal)	Approx 100%
Eyepoint	Approx 22mm
Dioptr Correction	Yes
Viewfinder Information	Customisable and toggle via INFO. Button (1) Liveview image with exposure info (2) Liveview image with basic info (3) Liveview image with full info Customisable settings: Grid overlay (x3 formats), Histogram (Brightness/ RGB), Electronic Level, Multi aspect ratios

## Depth of field preview

## LCD MONITOR

Type	7.5 cm (3.0") Touchscreen LCD (TFT). 3:2 aspect ratio. Approx. 1,040,000 dots. Electrostatic capacitive type. Vari-Angle
Coverage	Approx 100%
Brightness Adjustment	Adjustable to one of seven levels
Display Options	Customisable and toggle via INFO. Button (1) Liveview image with exposure info (2) Liveview image with basic info (3) Liveview image with full info Customisable settings: Grid overlay (x3 formats), Histogram (Brightness/ RGB), Electronic Level, Multi aspect ratios, Hints and Tips

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS M50 Mark II

<b>FLASH</b>			
<b>Built-in Flash GN (ISO 100, meters)</b>	5		
<b>Built-in Flash Coverage</b>	Maximum coverage at approx. 15mm (35mm equivalent: approx. 24mm)		
<b>Built-in Flash recycle time</b>	Approx. 3 seconds <sup>[4]</sup>		
<b>Modes</b>	Auto (E-TTL II)		
<b>Red-Eye Reduction</b>	Yes		
<b>X-sync</b>	1/200 sec		
<b>Flash Exposure Compensation</b>	+/- 2 EV in 1/3 increments		
<b>Flash Exposure Lock</b>	Yes		
<b>Second Curtain Synchronisation</b>	Yes		
<b>HotShoe/ PC terminal</b>	Yes/No		
<b>External Flash Compatibility</b>	E-TTL II with EX series Speedlites, wireless multi-flash support		
<b>External Flash Control</b>	Via camera setting/ flash setting menu		
<b>SHOOTING</b>			
<b>Modes</b>	Scene Intelligent Auto, Hybrid Auto, Creative Assist, SCN (Self-Portrait, Portrait, Smooth Skin, Landscape, Sports, Close-up, Food, Panning, Handheld Night Scene, HDR Backlight Control, Silent Mode), Creative Filters (Grainy B/W, Soft Focus, Fish-eye Effect, Water painting effect, Toy camera effect, Miniature effect, HDR Art standard, vivid, bold, embossed), Program AE, Shutter priority AE, Aperture priority AE, Manual exposure, Movie (Movie auto exposure, Movie manual exposure, Time-lapse movie)		
<b>Picture Styles</b>	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)		
<b>Colour Space</b>	sRGB and Adobe RGB		
<b>Image Processing</b>	Highlight Tone Priority (standard and enhanced) Auto Lighting Optimizer (4 settings) Long exposure noise reduction High ISO speed noise reduction (4 settings + Multi Shot NR) Lens peripheral illumination correction Chromatic aberration correction Diffraction correction Creative Assist: Presets Background Blur (5 settings) Brightness (19 levels) Contrast (9 levels) Saturation (9 levels) Color Tone 1 & 2 (19 levels) Monochrome (Off/Black and white/Sepia/Blue/Purple/Green)		
<b>Drive modes</b>	Single, High-Speed Continuous, Low-Speed Continuous, Self timer (2s, 10s, Remote)		
<b>Continuous Shooting</b>	One shot AF: Approx. 10 shots/sec for up to 36 frames in JPEG and 10 frames in RAW <sup>[5]</sup>		
<b>LIVE VIEW MODE</b>			
<b>Coverage</b>	Approx. 100% (horizontally and vertically)		
<b>FILE TYPE</b>			
<b>Still Image Type</b>	JPEG: Fine, Normal (Exif 2.31 compliant) / Design rule for Camera File system (2.0) RAW: RAW (CR3 14-bit), Digital Print Order Format [DPOF] Version 1.1 compliant		
<b>RAW+JPEG simultaneous recording</b>	Yes, RAW + various JPEG compression possible		
<b>Image Size</b>			RAW: (3:2) 6000 x 4000, (4:3) 5328 x 4000, (16:9) 6000 x 3368, (1:1) 4000 x 4000 JPEG 3:2: (L) 6000 x 4000, (M) 3984 x 2656, (S1) 2976 x 1984, (S2) 2400 x 1600 JPEG 4:3: (L) 5328 x 4000, (M) 3552 x 2664, (S1) 2656 x 1992, (S2) 2112 x 1600 JPEG 16:9: (L) 6000 x 3368, (M) 3984 x 2240, (S1) 2976 x 1680 (S2) 2400 x 1344 JPEG 1:1: (L) 4000 x 4000, (M) 2656 x 2656, (S1) 1984 x 1984, (S2) 1600 x 1600
<b>Movie Type</b>			MP4 [Video: MPEG-4 AVC/H.264, Audio: MPEG-4 AAC-LC (stereo)]
<b>Movie Size</b>			4K - 3840 x 2160 (23.98, 25 fps) Full HD - 1920 x 1080 (59.94, 50, 29.97, 25, 23.976 fps) HD - 1280 x 720 (119.9, 100, 59.94, 50 fps) Max duration 29min 59sec, Max file size 4GB
<b>Movie Length</b>			New folders can be created and selected
<b>Folders</b>			(1) Continuous, Auto Reset (2) Manual Reset
<b>File Numbering</b>			
<b>OTHER FEATURES</b>			
<b>Custom Functions</b>			9 customisable buttons
<b>Metadata Tag</b>			User copyright information (Author's Name, Copyright Details) Image rating (0-5 stars)
<b>Playback zoom</b>			15 steps plus smooth pinch-to-zoom
<b>Display Formats</b>			(1) Single image with information (toggle options) (2) Single image (3) Index display (4/9/36/100 images) (4) Jump Display (1/10/custom number image, by shot date, by rating, by folder, by movies only, protected only)
<b>Slide Show</b>			Playback time: 1/2/3/5/10/30 seconds Repeat: On/Off Transition Effects: Off, Slide in 1-2, Fade 1-3 Brightness/ RGB
<b>Histogram</b>			Yes
<b>Highlight Alert</b>			Yes
<b>Image Erase/Protection</b>			Erase: Single image, Selected images, Selected range, All images Protection: Selected images, Selected range, All images. Unprotect all images
<b>Menu Categories</b>			(1) Shooting menu (x8) (2) Playback menu (x4) (3) Setup menu (x5) (4) Display menu (5) My Menu
<b>Menu Languages</b>			29 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Vietnamese, Indonesian, Hindi, Japanese
<b>Firmware Update</b>			Firmware update possible by the user.
<b>INTERFACE</b>			
<b>Computer</b>			Hi-Speed USB (Micro USB) Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only, 1-11 ch) <sup>[6]</sup>
<b>Other</b>			Bluetooth® (Specification version 4.1, Bluetooth low energy technology) <sup>[7],[8]</sup> HDMI (Micro - Type-D connector), HDR output to compatible TV supported

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS M50 Mark II

## DIRECT PRINT

### Canon Printers

Canon Compact Photo Printers and PIXMA Printers supporting PictBridge

### PictBridge

Canon Compact Photo Printers and PIXMA Printers supporting PictBridge

## STORAGE

### Type

SD, SDHC, SDXC (UHS-I compatible)

## SUPPORTED OPERATING SYSTEM

### PC & Macintosh

See support pages for up-to-date information

## SOFTWARE

### Image Processing

Digital Photo Professional

### Other

Picture Style Editor, EOS Utility, Image Transfer Utility  
Camera Connect app available on iOS and Android devices<sup>[8]</sup>

## POWER SOURCE

### Batteries

1 x Rechargeable Li-ion Battery LP-E12

### Battery life

Viewfinder: Approx. 250 shots  
(at 23°C, AE 50%, FE 50%)<sup>[2]</sup>  
Live view: Approx 305 shots  
(at 23°C, AE 50%, FE 50%)<sup>[3]</sup>  
4K Movie Recording: Approx. 95 mins  
Full HD Movie Recording: Approx 130 mins  
Playback time when playing back a slideshow of still images: Approx. 3 hrs 45 mins

### Battery Indicator

4 levels

### Power saving

Display off (15, 30 sec or 1, 3, 5, 10, 30 mins)  
Auto Power Down (30 sec or 1, 3, 5, 10 mins, Disable)  
Viewfinder off (1, 3 min, disable)  
ECO mode

### Power Supply & Battery Chargers

Battery charger LC-E12  
Compact Power Adapter CA-PS700  
DC Coupler DR-E12

## PHYSICAL SPECIFICATIONS

### Body Materials

Polycarbonate

### Operating Environment

0 – 40 °C, 85% or less humidity

### Dimensions (WxHxD)

116.3 x 88.1 x 58.7mm

### Weight (body only)

Approx 387g (black), 388g (white), CIPA testing standard including battery and memory card

## ACCESSORIES

### Cases / Straps

Camera Jacket EH32-CJ (beige)  
Camera Jacket EH32-CJ (light brown)  
Neck Strap EM-E2 (light brown)  
Neck Strap EM-E2(BW) (brown)  
Neck Strap EM-E2(BK) (black)  
Neck Strap EM-E2(WH) (white)  
Neck Strap EM-200DB

### Lenses

EF-M lenses  
All EF and EF-S lenses compatible via Mount adapter EF-EOS M

### Flash

Canon Speedlites (including EL100, 90EX, 220EX, 270EX, 270EX II, 320EX, 380EX, 420EX, 430EX, 430EX II, 430EX III, 430EX III-RT, 470EX-AI, 550EX, 580EX, 580EX II, 600EX, 600EX-RT, 600EX II-RT, Macro-Ring-Lite, MR-14EX II, Macro Twin Lite MT-24EX, Speedlite Transmitter ST-E2, Speedlite Transmitter ST-E3-RT)  
Off-Camera Shoe Cord OC-E3, Speedlite Bracket SB-E2

### Remote Controller/ Switch

Bluetooth Remote BR-E1

### Other

Interface cable IFC-600PCU  
Mount Adapter EF-EOSM

All data is based on Canon standard testing methods except where indicated. Subject to change without notice.

### Footnotes:-

<sup>[1]</sup> Dual Pixel CMOS AF - AF is possible over an area of approx. 80% Vertical x 80% Horizontal of the frame

<sup>[2]</sup> Maximum number of AF frame is dependent on selected image aspect ratio

<sup>[3]</sup> Recommended Exposure Index

<sup>[4]</sup> When battery is fully charged

<sup>[5]</sup> Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Total number of frames captured and continuous shooting speed may vary depending on camera exposure settings, type of lens used, battery level, light level and memory card used.

<sup>[6]</sup> Wi-Fi use may be restricted in certain countries or regions.

<sup>[7]</sup> Equipped with Bluetooth® low energy technology. The Bluetooth® word mark and logos are registered trademarks owned by the

Bluetooth SIG, Inc. and any use of such marks by Canon Europe Ltd. is under license. Other trademarks and trade names are those of their respective owners.

<sup>[8]</sup> Bluetooth functionality with Camera Connect app requires smart device to be equipped with Bluetooth version 4.0 (or later). Also requires smart device to be using operating system iOS 8.4 (or later) or Android 5.0 (or later)

<sup>[9]</sup> Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated

Canon Ireland  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2052525  
canon.ie

Canon (UK) Ltd  
5 The Square  
Stockley Park  
Uxbridge  
UB11 1ET  
Tel: 01895 648 000  
www.canon.co.uk

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
Canon Europa NV 2021

Live for the story\_

# PUT YOUR PASSION IN THE SPOTLIGHT

# EOS M50 Mark II

If you're a content creator, the EOS M50 Mark II lets you communicate with your on-line audience on a whole new level. Perfect for vloggers, bloggers and influencers who want to step up from their smartphone and want to keep things simple and easy to use.

Sales Start Date: March 2021



#### PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
EOS M50 Mark II BK BODY GB	4728C033AA	8714574667911
EOS M50 Mark II BK M15-45 S GB	4728C034AA	8714574667928
EOS EOS M50 Mark II BK M15-45S+M55-200 GB	4728C035AA	8714574667935
EOS M50 Mark II BK M18-150 GB	4728C036AA	8714574667942
EOS M50 Mark II WH M15-45 S GB	4729C027AA	8714574667959

#### OPTIONAL ACCESSORIES:

Accessory Name	Mercury Code	EAN Code
<b>Power Supply</b>		
Battery Charger LC-E12E	6782B001AA	4960999913247
Battery Pack LP-E12	6760B002AA	4960999911625
Compact Power Adapter CA-PS700	7875A003AA	4549292054378
DC Coupler DR-E12	6785B001AA	4960999913278
<b>Cables</b>		
USB Cable IFC-600PCU	1015C001AA	4549292054378
<b>Miscellaneous</b>		
Body Cap Camera Cover R-F-4	6786B001AA	4960999913315
Directional Microphone DM-E1	1429C001AA	4549292065732
Stereo Microphone DM-E100	4474C001AA	4549292164992
Protecting Cloth PC-E2	2394C001AA	4549292099706
Wireless Remote-Control BR-E1	2140C001AA	4549292087864
Tripod Grip HG-100TBR	4157C001AA	4549292157956

The Canon logo in red, consisting of the word 'Canon' in its signature font.

Live for the story\_

# PUT YOUR PASSION IN THE SPOTLIGHT

# EOS M50 Mark II

If you're a content creator, the EOS M50 Mark II lets you communicate with your on-line audience on a whole new level. Perfect for vloggers, bloggers and influencers who want to step up from their smartphone and want to keep things simple and easy to use.



#### OPTIONAL ACCESSORIES:

Accessory Name	Mercury Code	EAN Code
<b>Cases, jackets &amp; straps</b>		
Body Jacket EH32-CJ Beige	2685C001AA	4549292109764
Body Jacket EH32-CJ Light Brown	2686C001AA	4549292109788
Neck Strap Black EM-E2 (BK)	1661C001AA	4549292078596
Neck Strap Brown EM-E2 (BW)	9930B001AA	4549292021257
Neck Strap Brown EM-E2 (BEIG)	1018C001AA	4549292053982
Neck Strap EM-200DB	9929B001AA	4549292021271
<b>Flash related accessories</b>		
Off Camera Shoe Cord OC-E3	1950B001AA	4960999417271
Speedlite Transmitter ST-E2	2478A004AA	4960999581538
Speedlite Transmitter ST-E3-RT	5743B003AB	4960999810232

#### MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
EOS M50 Mark II Black BODY GB	4728C033AA	EA	Each	1	16.8	16.8	13.7	0.747
		CT	Carton	6	42.9	35.5	20.5	5.47
		EP	Euro Pallet	150	120	80	117.5	147
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
EOS M50 Mark II BK M15-45 S GB	4728C034AA	EA	Each	1	16.8	16.8	13.7	0.903
		CT	Carton	6	42.9	35.5	20.5	6.41
		EP	Euro Pallet	150	120	80	117.5	170
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				

Live for the story\_

# PUT YOUR PASSION IN THE SPOTLIGHT

# EOS M50 Mark II

If you're a content creator, the EOS M50 Mark II lets you communicate with your on-line audience on a whole new level. Perfect for vloggers, bloggers and influencers who want to step up from their smartphone and want to keep things simple and easy to use.



#### MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
EOS EOS M50 Mark II BK M15-45S+M55-200 GB	4728C035AA	EA	Each	1	21.4	16.8	13.7	1.22
		CT	Carton	6	43	35.5	25.2	8.32
		EP	Euro Pallet	120	120	80	115.8	176
			Layers per Pallet	4				
			Cartons per Layer	5				
			Products per layer	30				
EOS M50 Mark II BK M18-150 GB	4728C036AA	EA	Each	1	16.8	16.8	13.7	1.07
		CT	Carton	6	42.9	35.5	20.5	7.42
		EP	Euro Pallet	150	120	80	117.5	196
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				
EOS M50 Mark II WH M15-45 S GB	4729C027AA	EA	Each	1	16.8	16.8	13.7	0.904
		CT	Carton	6	42.9	35.5	20.5	6.42
		EP	Euro Pallet	150	120	80	117.5	170
			Layers per Pallet	5				
			Cartons per Layer	5				
			Products per layer	30				

Live for the story\_

# PUT YOUR PASSION IN THE SPOTLIGHT

# EOS M50 Mark II

If you're a content creator, the EOS M50 Mark II lets you communicate with your on-line audience on a whole new level. Perfect for vloggers, bloggers and influencers who want to step up from their smartphone and want to keep things simple and easy to use.



## What's in the box?

### EOS M50 Mark II BLACK BODY

- EOS M50 Mark II Body (Black)
- Camera Cover R-F-4
- Strap EM-200DB
- Battery Charger LC-E12E
- Battery Pack LP-E12
- Terminal Cover
- Power cord(EU/SK)
- User Manual

### EOS M50 Mark II 15-45

- EOS M50 Mark II Body (Black)
- Camera Cover R-F-4
- EF-M15-45mm 1:3.5-6.3 IS STM
- Lens Cap E-49
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- Battery Pack LP-E12
- Terminal Cover
- Power cord(EU/SK)
- User Manual

### EOS M50 Mark II 15-45 + 55-200

- EOS M50 Mark II Body (Black)
- Camera Cover R-F-4
- EF-M15-45mm 1:3.5-6.3 IS STM
- Lens Cap E-49
- EF-M55-200mm 1:4.5-6.3 IS STM
- Lens Cap E-52 II
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- Battery Pack LP-E12
- Terminal Cover
- Power cord(EU/SK)
- User Manual

### EOS M50 Mark II 18-150

- EOS M50 Mark II Body (Black)
- Camera Cover R-F-4
- EF-M18-150mm 1:3.5-6.3 IS STM
- Lens Cap E-55
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- Battery Pack LP-E12
- Terminal Cover
- Power cord(EU/SK)
- Printed Matter Unit

### EOS M50 Mark II WHITE 15-45

- EOS M50 Mark II Body (White)
- Camera Cover R-F-4
- EF-M15-45mm 1:3.5-6.3 IS STM
- Lens Cap E-49
- Lens Dust Cap EB
- Strap EM-200DB
- Battery Charger LC-E12E
- Battery Pack LP-E12
- Terminal Cover
- Power cord(EU/SK)
- Printed Matter Unit

**Canon**

Live for the story\_