



Product Highlights:

- Streamline your workflow with transfer speeds up to 900MB/s¹
- USB 3.2 Gen 2 performance for blazing-fast transfers of large files and 8K video
- Built-in USB-C cable, plus a USB-C to USB-A adapter
- Supports CFexpress™ Type A cards up to 1TB
- Sturdy, heat-dissipating metal housing



TYPE-C



Quickly transfer from CFexpress™ Type A cards

The perfect partner for your CFexpress™ Type A cards, this reader lets you quickly offload 8K videos and large files with transfer speeds up to 900MB/s¹. It features a sturdy, heat-dissipating metal housing and supports cards with capacities up to 1TB.

Accelerate Your Workflow. Streamline your workflow with transfer speeds up to 900MB/s¹.

USB 3.2 Gen 2 Performance. Quickly offload 8K videos and large files with blazing-fast USB 3.2 Gen 2 performance.

For Type A and Type C Devices. With its built-in USB-C cable and a USB-C to USB-A adapter, the reader conveniently works with a wide range of devices.

Durable Metal Housing. Designed with a sturdy casing that not only looks good, but also provides excellent heat dissipation.

Supports Cards up to 1TB. With support for up to 1TB, this reader quickly offloads from even high capacity cards.

Rigorously Tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 27 years, Lexar has been a trusted leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

Lexar Retail Sku	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LRW515U-RNHNG	Global	843367132904	10843367132901	10
LRW515U-RNHNC	China	843367132911	10843367132918	

Specifications

Performance	Up to 900MB/s read ¹ , up to 800MB/s write ¹
Drivers	No driver required, plug-and-play, hot-plug support
Dimensions (W x L x H)	60mm x 45mm x 15mm
Operating Temperature	0° to 40° C (32°F to 104°F)
Storage Temperature	-25°C to 85°C (-13°F to 185°F)
Systems Supported	Mac® OS 10.8+, Windows® 11/10/8/7/Vista/XP, USB 2.0+
Warranty	2-year limited

¹Results may vary based on system configuration and card speed.

Lexar is not liable for any loss of data or images.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

Security safeguards, by their nature, are capable of circumvention. Lexar does not guarantee data will be 100% secure from unauthorized access, alteration, or destruction.

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.