



Product Highlights:

- Blazing-fast USB 3.2 Gen2x2 performance of up to 2000MB/s read and 2000MB/s write¹ (Performance on Mac and other systems not supporting USB 3.2 Gen 2x2 may be lower)
- Features a durable aluminum enclosure with a sandblasted finish for added protection and shock and vibration resistance²
- Includes Lexar® DataShield™, a 256-bit AES encryption software solution to protect files³
- Includes USB Type-C and USB Type-A cables
- Carabiner loop to secure the drive to your pack or bag

Capacities:

2TB
(up to 2000MB/s read, 2000MB/s write¹)

1TB
(up to 2000MB/s read, 2000MB/s write¹)

512GB
(up to 2000MB/s read, 2000MB/s write¹)



Superior Performance for Creative Professionals

The Lexar® Professional SL600 Portable SSD delivers 2000MB/s read/write speeds¹ so it's perfect for photographers, videographers, and content creators. It also features a durable aluminum enclosure for extra protection traveling or in the studio. Lexar DataShield™ software keeps your files secure with 256-bit AES encryption. For convenience, the drive includes USB Type-C and USB Type-A cables and features a carabiner loop to secure it to your bag.

Powerful Performance. Blazing-fast USB 3.2 Gen2x2 performance of up to 2000MB/s read/write speeds¹ for accelerated data transfers.

Sleek and Solid. A durable aluminum enclosure with a sandblasted finish gives this drive style plus added protection and shock and vibration resistance².

Keep Your Files Secure. Includes Lexar DataShield, with 256-bit AES encryption, to help keep your sensitive files secure³.

Plays Nicely with all Your Devices. Includes USB Type-C and USB Type-A cables for compatibility across all your professional devices.

Strap in and Go. Designed with a carabiner loop so you can secure the drive to your travel bag when you're on the go.

Rigorously tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 27 years, Lexar has been trusted as a leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

Lexar Retail Sku	Capacity	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LSL600X512G-RNBNG	512GB	Global	843367131600	10843367131607	10
LSL600X001T-RNBNG	1TB		843367131617	10843367131614	
LSL600X002T-RNBNG	2TB		843367131624	10843367131621	

¹Up to 2000MB/s read and write speeds. Speeds based on internal testing on device that supports USB 3.2 Gen 2x2; performance may be lower depending on host device, interface, usage conditions, and other factors. 1MB = 1,000,000 bytes.

²Shock resistance (1500G, duration 0.5ms, Half Sine Wave) and vibration resistance (10~2000Hz, 20g, 1 Oct/min, 30min/axis (X, Y, Z)). Based on internal testing. Actual performance may vary.

³Security safeguards, by their nature, are capable of circumvention. Lexar does not guarantee data will be 100% secure from unauthorized access, alteration, or destruction.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.
Lexar is not liable for any loss of data or images.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Specifications

Capacity	512GB, 1TB, 2TB
Interface	USB 3.2 Gen2x2
Speed	up to 2000MB/s read, up to 2000MB/s write ¹
Operating Temperature	0°C to 70°C (32°F to 158°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Module Size	112.6 x 59 x 10.6 mm (4.433" x 2.323" x 0.417")
Warranty	Five-year limited warranty

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.