

SPEEDLITE EL-10

STEP INTO

A NEW

LIGHT

The SPEEDLITE EL-10 is the perfect companion for a hobbyist photographer, enabling better control and intelligent communication with the camera for more creative photography.

24-105mm flash coverage

Category-leading 1.5s recharge time

Bounce up 90°, left 150° and right 180°

Catchlight panel

Power down to 1/1024

Custom light emission mode with C1/C2/C3 linked to camera mode



Bring your portraits to life

Control the light with a horizontal and vertical bounce, and a versatile power range of 1/1 to 1/1024 for a softer look. Plus, get that extra sparkle in the eye thanks to a catchlight panel.



Intelligent and intuitive

The 21-pin multi-function foot enables quick communication with the EOS R-system cameras. Adjust settings straight from your camera screen, preset up to three custom modes, and even operate remotely through your Camera Connect App.



Empower your creativity

The SPEEDLITE EL-10 is your trusted companion, with a wireless camera flash that recharges in just 1.5 seconds, 24-105mm of zoom coverage, and a powerful output with a guide number of 40.



Shoot with confidence

Powered by four AA batteries, this Speedlite flashgun will last at least 260 full power shots. Keep an eye on your battery level and easily adjust settings on the LCD panel, even when the light drops.



Lightweight and adaptable

Tweak your settings on the go with the electronic dial, or enable the E-TTL II auto flash to instantly adjust to the correct exposure. It's also light to carry – perfect for travel or for a longer shoot.

PRODUCT RANGE



Canon Speedlite EL-1



Canon Speedlite EL-5



SPEEDLITE EL-10

Power	
Guide No. (ISO100).meters	40
Zoom	
Zoom head	Auto/Manual
Focal length coverage	24-105mm
Coverage with wide panel	14mm
Auto zoom for sensor size	Yes
Flash modes	
Auto exposure control	E-TTL II / E-TTL
High speed sync (FP)	Yes
Manual / output settings	Yes - 1/1 to 1/1024 ¹
Manual steps	1/3-stops
Continuous shooting priority (CP) mode	-
Continuous flashes in a burst	Maximum at full power: Approx. 65 ²
Strobe / output settings	Not supported
Stroboscopic Frequency	Not supported
Flash-related function	
FE lock	Yes
FE memory	Yes
Flash exposure compensation	±3 stops
Flash exposure bracketing	±3 stops
Second-curtain flash sync	Yes (including wireless) ³
Modelling flash	No (supported as off-camera receiver unit only) ⁴
Modelling lamp	No
Colour temperature info communication	Yes
Wireless flash	
Transmitter	Yes
Transmission type	Radio only
Transmitter range	30m (approx.) ⁵
Receiver	Yes
Max. number of Transmitters / Receivers	15/15 (16 in total of any combination)
No. of groups	5 (A/B/C/D/E)
No. of channels	Auto, 1-15
LINKED Remote Shutter Release	Yes
Flash head movement	
Up	45, 60, 75, 90 °
Down	0 °
Left	60, 75, 90, 120 and 150 °
Right	60, 75, 90, 120, 150 and 180 °
AF Assist	
AF-assist beam	Flash strobe
Number of AF points supported (infrared)	n/a
AF-assist range (at centre)	0.7 - 10m

Power source	
Battery	4 x AA batteries ⁶
Battery level indicator	No
Minimum recycling time	Approx. 0.1-2.5 ⁷
No. of flashes (new batteries)	210-1400 ²
External power supply	No
Construction	
Dust and water resistance	No
Active cooling	No
Mount type supported	Multi-Function Shoe ⁸
Misc.	
Custom Functions (C.Fn) / Personal Functions (P.Fn)	11 x C.Fn / 8 x P.Fn (plus 3 x Custom Modes (C1, C2, C3))
Flash settings from camera menus	Yes ⁹ - On-flash Menu Direct button
External flash exposure sensor	No
PC terminal	No
Accessories	
Included	Speedlite Case Mini Stand Mounting foot cover Speedlite Transmitter ST-E10 (Multi-Function foot) Speedlite Transmitter ST-E3-RT (Ver.2) (Standard 5-pin foot) Color Filters SCF-E2 Off-camera shoe cord OC-E4A
Optional	
Dimensions & weight	
Size (W x H x D), mm	Approx. 70.6 x 116.3 x 98.3 mm
Weight, grams	287

FOOTNOTES

- Minimum flash output is 1/128 for high-speed sync.
- When using new AA/LR6 alkaline batteries, based on Canon standards and set to manual flash. Continuous flash count at full output until flash firing restriction Level 1.
- With compatible cameras/devices and not available with stroboscopic shooting.
- Modeling flash cannot be used when mounted on a camera
- Without any obstructions between sender and receiver, and without external radio interference. Arrangement of units and other external factors may affect the range/performance.
- LR6 alkaline or HR6 Ni-MH type batteries can be used. FR6 lithium batteries cannot be used.
- 1/1024 to 1/1 power charging time required for firing.
- For use with compatible cameras with Canon's Multi-Function shoe, a firmware update may be required. Note, not all functions may be supported with all cameras (the EOS R5 C and camcorders with the Multi-Function shoe are not supported).
- With compatible cameras.

**STEP INTO
A NEW LIGHT**

SPEEDLITE EL-10

The SPEEDLITE EL-10 is the perfect companion for a hobbyist photographer, enabling better control and intelligent communication with the camera for more creative photography.

Sales Start Date: June 2024



Product details

Product Name	Mercury Code	EAN Code
SPEEDLITE EL-10	6579C002AA	

**STEP INTO
A NEW LIGHT**

SPEEDLITE EL-10

The SPEEDLITE EL-10 is the perfect companion for a hobbyist photographer, enabling better control and intelligent communication with the camera for more creative photography.



Measurement / logistic information

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Net Weight (kg)	Gross Weight (kg)
SPEEDLITE TRANSMITTER EL-10	6579C002AA	EA	Each	1	9.5	7.8	18.2	0.392	0.4495
		CT	Carton	6	60	33.3	24.3	-	3.71
		EP	Euro Pallet	120	120	80	134.5	-	89.2
			Layers per Pallet	5					
			Cartons per Layer	4					
			Products per Layer	24					

**STEP INTO
A NEW LIGHT**

SPEEDLITE EL-10

The SPEEDLITE EL-10 is the perfect companion for a hobbyist photographer, enabling better control and intelligent communication with the camera for more creative photography.



What's in the box

Speedlite EL-10

- Speedlite EL-10
- Soft Case
- Mini Stand
- User Manual
- Packing Unit



