

## GOLD CFexpress<sup>™</sup> 4.0 Type B Card



#### **Product Highlights:**

- Impressive PCle 4.0 performance delivers 3600MB/s max read, 3300MB/s max write<sup>1</sup>
- Shoot cinema-quality video with no dropped frames with sustained write speeds of 3000MB/s<sup>1</sup>
- Optimize your workflow and increase productivity by pairing this card with the Lexar Professional Workflow CFexpress™ 4.0 Type B Card Reader (sold separately)
- Rugged design: temperature-proof, vibration-resistant, 12,000x wear-out resistant, dust-resistant (IP5X), 5m drop-proof, shock-resistant, bend-resistant, and 7x more compression-resistant than SD cards<sup>4</sup>
- Generous capacities up to 4TB
   accommodate even extended videography sessions, minimizing the need to change cards
- Includes access to Lexar Recovery Tool software and a limited lifetime warranty<sup>2</sup> for extra peace of mind

#### Capacities

**512**GB

**1**TB

**2**TB

**4**TB









## **Cutting-Edge Performance for Videography**

Experience the CFexpress<sup>™</sup> 4.0 advantage and capture stunning, seamless, cinema-quality 8K RAW video with write speeds up to 3300MB/s¹ and dramatically expedite post-production with read speeds up to 3600MB/s. Equipped with 8-point protection against temperature, vibration, wear-out, dust (IP5X), drops, shocks, compression, and bends, the card also comes with data recovery software and a limited lifetime warranty.²

**Impressive Pro Performance.** PCle 4.0 technology delivers 3600MB/s max read and 3300MB/s max write speeds, <sup>1</sup> to capture vibrant, fast-action shots and then power through post-production.

**Stunning Sustained Write Speeds.** 3000MB/s sustained write speeds<sup>1</sup> let you shoot commercial-quality video with no dropped frames and capture stutter-free burst-mode photos, shot after shot.

**Accelerate your Workflow by 2x^3.** Paired with the Lexar Professional Workflow CFexpress  $4.0^{\text{TM}}$  Type B Card Reader (sold separately), this card enables you to dramatically expedite your post-production process to twice as fast as CFexpress 2.0 cards

**Built to Withstand Harsh Environments.** The Lexar® Professional GOLD CFexpress™ 4.0 Type B Card features a rugged design that is temperature-proof, vibration-resistant, 12,000x wear-out resistant, dust-resistant (IP5X), 5m drop-proof, shock-resistant, bend-resistant, and 7x more compression-resistant than SD cards.⁴

**More Room for Your Creativity.** With a massive capacity of up to 4TB, you can experience unrivaled performance that lets you shoot and record continuous, seamless, 8K RAW video, resulting in a more efficient workflow.

**We've Got You Covered.** The Lexar Recovery Tool helps you recover accidentally deleted and formatted pictures or video files and a limited lifetime warranty<sup>3</sup> provides extra peace of mind.

**Rigorously Tested.** All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

Warning: CFexpress™ Type B cards are only compatible with devices that support the CFexpress™ format. Highest transfer speed achieved only when used with a CFexpress™ Type B reader, indicated by a boxed USB logo on the product. Contact your device manufacturer for details.

Vibration Resistant: 10~2000Hz

Wear-out resistance: up to 12,000 times of plugging and unplugging

IP5X Dust-resistant 5-meter drop-proof

Shock Resistant: 1500G shock

70N compression resistance

Lexar is not liable for any loss of data or images

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

#### www.lexar.com

©2024 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

<sup>&</sup>lt;sup>1</sup> Up to 3600MB/s read transfer, write speeds lower. Speeds based on internal testing. Actual speed may vary depending on host device.

<sup>&</sup>lt;sup>2</sup> Limited lifetime warranty is limited to 10 years from purchase in Germany and regions not recognizing lifetime warranty

<sup>&</sup>lt;sup>3</sup> Temperature-Proof: Operation -12°to 72°C, Storage -25°C to 85°C



# GOLD CFexpress<sup>™</sup> 4.0 Type B Card

For more than 28 years, Lexar has been trusted as a leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

### **Specifications**

Capacity	512GB, 1TB, 2TB, 4TB			
	<b>4TB</b> – 3600MB/s max read, 3300MB/s max write, 3000MB/s sustained write <sup>1</sup>			
Performance	<b>2TB</b> – 3600MB/s max read, 3300MB/s max write, 3000MB/s sustained write <sup>1</sup>			
Terrormance	<b>1TB</b> – 3600MB/s max read, 3300MB/s max write, 3000MB/s sustained write <sup>1</sup>			
	<b>512GB</b> – 3600MB/s max read, 3300MB/s max write, 3000MB/s sustained write <sup>1</sup>			
Form Factor	CFexpress™ 4.0 Type B			
Interface	PCle Gen 4			
Operating Temperature	- 12° to 72°C (10.4°F to 161.6°F)			
Storage Temperature	- 25° to 85°C (- 13°F to 185°F)			
Dimensions (W x L x H)	29.6mm x 38.5mm x 3.8mm / 1.16"x 1.51"x 0.14"			
Weight	7.8g / 0.017lbs			
Warranty	Limited lifetime warranty <sup>2</sup>			

Lexar Retail SKU	Capacity	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LCXEXP4512G-RNENG	512GB	Global	843367135837	10843367135834	10
LCXEXP4001T-RNENG	1TB	Global	843367135844	10843367135841	10
LCXEXP4002T-RNENG	2TB	Global	843367135851	10843367135858	10
LCXEXPR004T-RNENG	4TB	Global	843367134335	10843367134332	10

#### www.lexar.com

©2024 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.